



STATEMENT OF COMPLIANCE

INSPECTOR	
CERTIFICATE HOLDER/APPLICANT	

Nig.CARs 12 Vol ii	Requirement of the Regulation	Compliance Method Manual Ref #	Certificate holder/ Applicant Comments (if appropriate)	Status
12.1.1	GENERAL			
12.1.1.1	APPLICABILITY (a) This part shall apply to the certification and operation of heliports in Nigeria with the exception of military heliports. OPERATION OF HELIPORTS (b) No person shall operate a heliport (mobile or fixed) for the take-off and landing of helicopters in Nigeria unless he is a holder of a Heliport Certificate (HC) granted under these Regulations for the said operation.			
12.1.1.2	EXEMPTIONS (a) The Authority may exempt, in writing, a heliport operator from complying with specific provisions of these Regulations. (1) Before the Authority decides to exempt the Heliport Operator, the Authority will take into account all safety related aspects.			



STATEMENT OF COMPLIANCE

	<p>(2) An exemption is subject to the heliport operator complying with the conditions and procedures specified by the Authority in the Heliport Certificate as being necessary in the interest of safety.</p> <p>(b) Deviation from these Regulations and the conditions and procedures referred to in paragraph 12.1.1.2(a)(2) shall be set out in an endorsement on the Heliport Certificate and reported in the Aeronautical Information Publication (AIP).</p>			
12.1.1.3	<p>DEFINITIONS</p> <p>(a) Part 12 Volume I subpart 1 contains definitions for the terms which are used in this regulation. Those definitions are not reproduced in this Volume, with the exception of the following two, which are included for ease of reference:</p>			
12.1.1.5	<p>ESTABLISHMENT OF HELIPORTS IN NIGERIA</p> <p>(a) The Minister may approve the establishment and development of heliport anywhere in Nigeria;</p> <p>(b) Roads, approaches, apparatus, equipment, buildings and other accommodations in connection to such heliports shall be maintained by the owners in conformity with these regulations and any other requirement as may be prescribed by the Authority from time to time.</p>			
12.1.1.6	<p>DESIGN/OPERATION OF HELIPORTS</p> <p>(a) No person or corporate entity shall commence construction or reconstruction of an heliport without approval of the Authority.</p> <p>(b) Pursuant to 12.1.1.6(a), the Heliport operator shall submit to the Authority the following information for assessment:</p> <p>(1) heliport layout and Markings, lights and signs plans; (2) architectural drawings of the terminal and other operational buildings.</p>			



STATEMENT OF COMPLIANCE

	<p>(c) No person shall operate a heliport in Nigeria (mobile or fixed) for the take-off and landing of helicopters engaged in flights unless such a person is a holder of a Heliport Certificate granted under these Regulations.</p>			
12.1.1.7	<p>RESTRICTIONS / PROHIBITIONS</p> <p>(a) Except with the approval by the Authority, no helicopter shall operate at a heliport.</p> <p>(b) No heliport operator shall operate in the night except for emergency purposes granted by the Authority.</p> <p>(c) Subject to the approval, the Authority will restrict or prohibit flights at any heliport at which aviation facilities for emergency night flights are lacking; or where the terrain, landing surface conditions or other objects in the vicinity of the heliport could cause a hazard to the operation of helicopters.</p> <p>(d) The Authority will restrict or prohibit operation at an Heliport either absolutely or subject to any exceptions or conditions that the Authority will specify, if the restriction is necessary for aviation safety and/or in the public interest.</p>			
12.1.2	HELIPORT CERTIFICATION			
12.1.2.1	<p>REQUIREMENT TO HOLD HELIPORT CERTIFICATE</p> <p>(a) The operator of a heliport intended for landing and take-off of helicopters in Nigeria shall be in possession of a heliport certificate. This also applies to heliports owned by Corporate entities engaged in business activities.</p> <p>(b) A person shall not operate a Heliport if the Heliport is not certified by the Authority.</p>			



STATEMENT OF COMPLIANCE

12.1.2.2	<p>APPLICATION FOR HELIPORT CERTIFICATE</p> <p>An application for the issuance of heliport certificate shall be:</p> <ul style="list-style-type: none"> (a) made to the Authority in the appropriate form as prescribed by the Authority. (b) accompanied by:— <ul style="list-style-type: none"> (1) the heliport manual; and statement of compliance demonstrating the heliport Operator's manual is in compliance with the relevant provisions in this volume. (2) the plans of heliport; including obstacle chart A showing details of obstructions marked /lighted (3) security clearance from the Federal Government ; (4) written approval from the town planning authority where applicable; (5) Environmental Impact Assessment approval from the (relevant State entity); (6) proof of payment of the appropriate fee prescribed by the Authority; and (7) adequate insurance cover. (8) Particulars of non-compliance with, or deviations from the standards prescribed in this Regulation. 			
12.1.2.3	<p>GRANT OF HELIPORT CERTIFICATE</p> <p>The Authority may approve the application and accept the heliport manual of the applicant for a heliport certificate subject to the provisions in this section and grant a Heliport Certificate to an applicant if:</p> <ul style="list-style-type: none"> (a) the Heliport facilities and equipment are in accordance with the applicable heliport standards; (b) The heliport manual prepared for the applicant's heliport accurately describes the facilities, services and equipment at the Heliport. 			



STATEMENT OF COMPLIANCE

	<p>(c) the heliport operating procedures make satisfactory provision for the safety of helicopters;</p> <p>(d) the applicant would, if granted a certificate, have the necessary competence, experience and resources to operate and maintain the heliport;</p> <p>(e) an acceptable safety management system is in place at the heliport.</p>			
12.1.2.4	<p>REFUSAL TO GRANT HELIPORT CERTIFICATE</p> <p>If the Authority refuses to grant a heliport certificate to an applicant, the Authority will give the applicant notice of the refusal, and the reasons for it, not later than 14 days from the date of refusal.</p>			
12.1.2.5	<p>DURATION OF HELIPORT CERTIFICATE</p> <p>A heliport certificate shall remain in force for a period of one year unless suspended or cancelled by the Authority.</p>			
12.1.2.6	<p>RENEWAL OF HELIPORT CERTIFICATE</p> <p>A heliport operator shall ensure that renewal of his heliport certificate is commenced not less than 90 days to the date of expiration of his certificate.</p>			
12.1.2.7	<p>ENDORSEMENT OF HELIPORT CERTIFICATE</p> <p>The Authority, when granting the heliport certificate shall endorse the conditions for the type and use of the heliport and other details as contained in the heliport certificate.</p>			
12.1.2.8	<p>AMENDMENT OF HELIPORT CERTIFICATE</p> <p>The Authority may amend the heliport certificate when:</p> <p>(a) there is a change in the ownership and management of the heliport; or</p> <p>(b) there is a change in the use or operation of the heliport; or</p> <p>(c) there is a change in the boundaries of the heliport; or</p> <p>(d) the holder of the heliport certificate makes a request for an amendment</p>			



STATEMENT OF COMPLIANCE

12.1.2.9	<p>VOLUNTARY SURRENDER OF HELIPORT CERTIFICATE</p> <p>The Authority may cancel a heliport certificate if the heliport operator voluntarily gives notice, in writing, to surrender his/her heliport certificate:</p> <p>(a) the heliport certificate holder shall give the Authority 30 days written notice of the date on which the certificate is to be surrendered in order that suitable promulgation action can be taken;</p> <p>(b) The Authority will cancel the certificate on the date specified in the notice.</p>			
12.1.2.10	RESERVED			
12.1.2.11	<p>INTERIM HELIPORT CERTIFICATE</p> <p>(a) The Authority may issue an interim heliport certificate to the applicant of a heliport certificate referred to in these Regulations, authorizing the applicant to operate an heliport if the Authority is satisfied that</p> <p>(1) an heliport certificate in respect of the heliport will be issued to the applicant as soon as the applicant procedure for the grant of an Heliport Certificate has been completed; and</p> <p>(2) the grant of the interim certificate is in the public interest and is not detrimental to aviation safety.</p> <p>(b) EXPIRATION OF INTERIM HELIPORT CERTIFICATE</p> <p>An interim heliport certificate issued pursuant to paragraph 12.1.2.11 shall expire on;</p> <p>(1) the date on which the heliport certificate is issued or</p> <p>(2) the expiry date specified in the interim heliport certificate; whichever is earlier.</p>			



STATEMENT OF COMPLIANCE

	<p><i>Note: These Regulations apply to an interim heliport certificate in the same manner as they apply to a heliport certificate.</i></p>			
12.1.2.12	<p>SUSPENSION OR REVOCATION OF HELIPORT CERTIFICATE</p> <p>(a) The Authority may, by written notice given to the holder of an heliport certificate, suspend an Heliport certificate for any of the following reasons:</p> <p>(1) a condition to which the certificate is subject has been breached ;</p> <p>(2) the heliport facilities, operations or maintenance are not of the requirement in the interests of the safety of air navigation;</p> <p>(3) the heliport operator's safety management system is found to be inadequate;</p> <p>(4) it is in the interest of operational safety;</p> <p>(5) all other means for timely correction of the unsafe condition or ensuring safe aircraft operations have not yielded the required results;</p> <p>(6) the technical proficiency or qualifications of the heliport operator to perform the duties to meet the critical safety requirements in accordance with the Regulations are found inadequate;</p> <p>(7) the operator resists or is unwilling to take action to correct or mitigate the condition affecting aviation safety;</p> <p>(8) the operator willfully fails to perform an already agreed upon corrective action and suspension of the certificate is the last resort to avoid unsafe operations.</p> <p>(b) The Authority may, by written notice given to the holder of an heliport certificate, revoke a heliport certificate for any of the following reasons:</p> <p>(1) the heliport operator is incapable or unwilling to carry out corrective action or has committed serious violations repeatedly;</p> <p>(2) the heliport operator has demonstrated a lack of responsibility, such as deliberate and flagrant acts of non-compliance or falsification of records jeopardizing aviation safety;</p>			



STATEMENT OF COMPLIANCE

	<p>(3) the heliport operator has made it convincingly clear that the continued operation of the heliport will be detrimental to the public interest.</p> <p>(c) SHOW CAUSE NOTICE: Before suspending or revoking a heliport certificate, the Authority will give to the holder a “show cause notice” that :</p> <p>(1) sets out the facts and circumstances that, in the opinion of the Authority, would justify the suspension or revocation; (2) invites the holder to show cause, in writing, within 14 days, after the date of the notice, why the certificate should not be revoked or suspended ;</p> <p>(d) The Authority will take into account any written submission that the holder makes to the Authority within the time allowed.</p>			
<p>12.1.3</p>	<p>HELIPORT MANUAL</p>			
<p>12.1.3.1</p>	<p>PREPARATION OF HELIPORT MANUAL</p> <p>(a) The heliport operator shall have a manual, to be known as the Heliport manual which shall:</p> <p>(1) be typewritten or printed, and signed by the heliport operator; (2) be in a format that is easy to revise; (3) have a system for recording the currency of pages and amendments thereto, including a page for logging revisions; and (4) be organized in a manner that will facilitate the preparation, review, acceptance and approval process. (5) Contain all pertinent information concerning the heliport site, facilities, services, equipment, Operating procedures, Organization and management;</p> <p>(6) Demonstrate that the heliport conforms to specifications of Subpart 2 of this Volume.</p>			



STATEMENT OF COMPLIANCE

	(7) Take the form and contains information as detailed in Nig. CARs Part 12 vol II, IS:12.1.3.3 .			
12.1.3.2	<p>LOCATION OF HELIPORT MANUAL</p> <p>(a) the heliport operator shall provide the Authority with a complete and current copy of the heliport manual.</p> <p>(b) the operator shall keep at least one complete and current copy of the heliport manual at the heliport and one copy at the operator's principal place of business if other than the Heliport.</p> <p>(c) the heliport operator shall make the complete and current copy of the heliport manual available for inspection by authorized officers of the Authority.</p>			
12.1.3.3	<p>INFORMATION TO BE INCLUDED IN THE HELIPORT MANUAL</p> <p>(a) The operator of the heliport shall include the following particulars in a heliport manual as provided by IS:12.1.3.3, to the extent that they are applicable to the heliport, under the following parts:</p> <p>(1) General information on the purpose and scope of the heliport manual; the legal requirement for a heliport certificate and a heliport manual as prescribed in the Regulations; conditions for use of the heliport; the aeronautical information services available and the procedures for their promulgation; the system for recording helicopter movement and the obligations of the heliport operator.</p> <p>(2) Particulars of the heliport site.</p> <p>(3) Particulars of the heliport required to be reported to the aeronautical information service;</p> <p>(4) The heliport operating procedures and safety measures;</p> <p>(5) Details of the heliport administration and the safety management</p>			



STATEMENT OF COMPLIANCE

	<p>system;</p> <p>(6) Details of heliport rescue and firefighting;</p> <p>(7) Particulars of environmental protection;</p> <p>(8) Programme for the heliport ATS;</p> <p>(9) The procedures to control, amend and distribute the heliport manuals</p> <p>(b) If the Authority exempts the heliport operator from complying with any requirement set out in the Regulations, the heliport manual shall show the identifying number given to that exemption by the Authority and the date the exemption came into effect and any conditions or procedures subject to which the exemption was granted.</p> <p>(c) If a particular is not included in the heliport manual because it is not applicable to the heliport, the Heliport operator must state in the manual the reasons for the non-applicability of the particular.</p> <p>(d) The operator of an Heliport shall operate the Heliport in accordance with the heliport manual.</p>			
12.1.3.4	<p>FORM OF HELIPORT MANUAL</p> <p>The heliport operator shall keep the copies of the heliport manual required by these Regulations in a printed form. Other copies may be kept in an electronic form.</p>			
12.1.3.5	<p>AMENDMENTS OF HELIPORT MANUAL</p> <p>(a) The heliport operator shall amend the heliport manual whenever it is necessary to do so, to maintain the currency of the manual.</p> <p>(b) The Authority may give written directives to the heliport operator requiring the operator to amend the heliport manual if necessary.</p> <p>(c) The operator of a certified heliport shall comply with the directive given to the operator by the Authority in paragraph 12.1.3.5(b)</p>			
12.1.3.6	<p>NOTICE OF AMENDMENTS</p> <p>(a) The heliport operator shall inform the Authority, in writing, of any amendment to the heliport manual within 30 days.</p>			



STATEMENT OF COMPLIANCE

12.1.3.7	<p>THE AUTHORITY'S APPROVAL OF HELIPORT MANUAL</p> <p>(a) The Authority will approve the heliport manual and any amendments thereto, provided they meet the requirement of this subpart.</p>			
12.1.3.8	<p>HELIPORT MANUAL CONTROLLER</p> <p>(a) The heliport operator shall appoint a person to be the heliport manual controller, whose functions shall include:</p> <p>(1) keeping a record of persons who hold copies of the whole or part of the Heliport Manual;</p> <p>(2) updating of information in the manual given to those holders referred to in paragraph 12.1.3.8(a)(1).</p>			
12.1.3.9	<p>ADDITIONAL REQUIREMENT</p> <p>(a) Additional requirement related to heliport manual is given in IS: 12.1.3.3</p>			
12.1.4	<p>OBLIGATIONS OF THE HELIPORT OPERATOR</p>			
12.1.4.1	<p>COMPLIANCE WITH STANDARDS AND PRACTICES</p> <p>(a) A Heliport operator shall comply with the requirements with respect to the heliport as a whole, the heliport standards as published by the Authority.</p>			
	<p>COMPETENCE OF OPERATIONAL AND MAINTENANCE PERSONNEL</p>			



STATEMENT OF COMPLIANCE

	<p>(a) The heliport operator shall employ an adequate number of qualified and skilled personnel to perform all critical activities for heliport operation and maintenance.</p> <p>(b) The operator shall train all operational and maintenance personnel who access safety areas and perform duties in compliance with the this Regulation. This training shall be completed prior to the initial performance of such duties and at least be retrained once every 3 years. The curriculum for initial and recurrent training shall include at least the following areas :</p> <p>(1) heliport familiarisation, including marking, lighting, and signs system; (2) Procedures to access an operation/safety areas; (3) Heliport Emergency Plan; (4) heliport communications, including radio communication, where applicable, between the air traffic control tower and personnel, use of the common traffic advisory frequency if there is no air traffic control tower or the tower is not in operation, and procedures for reporting unsafe heliport conditions; (5) Duties required under the Heliport Manual and the requirements of this regulation; (6) In respect of Heliport maintenance, the training of personnel shall include the following areas as appropriate:</p> <p>(i) Maintenance of the paved and unpaved areas; (ii) Heliport safety areas; (iii) Heliport drainage and fencing; (iv) Heliport Visual aids; (v) Passenger building facilities.</p> <p>(c) The operator shall keep a record of all training completed by each individual. This shall, at a minimum, a description and date of training received and provide the Authority with a copy of this record, if requested ;</p> <p>(d) The operator shall, as appropriate, comply with the following training requirements:</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>(1) Aircraft Rescue and Fire Fighting operational requirements; (2) heliport Inspection programme ; (3) Wildlife Hazard management (where applicable).</p> <p>(e) The heliport operator shall implement a programme to upgrade the competency of the personnel.</p> <p>(f) The Heliport operator shall submit to the Authority, training programmes for operational and maintenance personnel for acceptance.</p>			
12.1.4.3	<p>HELIPORT OPERATION AND MAINTENANCE.</p> <p>(a) The heliport operator shall maintain the heliport in accordance with the procedures set out in the approved heliport manual;</p> <p>(b) To ensure the safety at the Heliport, the Heliport operator shall:</p> <p>(1) Provide and maintain navigational visual aids which includes: wind direction indicators, lights, markings, markers and signs on the Heliport as prescribed in the Subpart 2 of this Volume.</p> <p>(2) maintain heliport surfaces and provide proof of friction tests on heliport where applicable (minimum friction coefficient value of 0.65).</p> <p>(3) carryout the 75kg hammer drop test on helideck safety net. (4) submit/implement a corrective action plan for mitigating the safety concerns at Heliport.</p> <p>(c) carry out checks, preventive maintenance and repairs on the heliport facilities, using a maintenance programme ;</p> <p>(d) co-ordinate work and ensure compliance with safety requirements for routine maintenance, minor or major construction or maintenance work at the Heliport in line with the procedures in this Regulation and related guidance material ;</p>			



STATEMENT OF COMPLIANCE

	<p>(e) co-ordinate with the ATS provider in order to be satisfied that appropriate air traffic services are available to ensure the safety of helicopters in the airspace associated with the Heliport. The coordination shall cover other areas related to safety such as aeronautical information service, meteorological service and aviation security;</p> <p>(f) A Heliport operator intending to make weather reports from Automatic Weather systems (AWOS) shall apply to the Authority for permit.</p>			
12.1.4.4	<p>HELIPORT OPERATOR'S SAFETY MANAGEMENT SYSTEM.</p> <p>(a) The heliport operator shall:</p> <p>(1) Implement a Safety management system acceptable to the Authority as prescribed in Nig. CARs Part 20.</p> <p>(2) have and put in effect, a safety management system that includes the policies, procedures and practices necessary to provide the services covered by its approval safely;</p> <p>(3) oblige all users of the Heliport to comply with the requirements laid down by the Heliport operator with regard to safety at the Heliport;</p> <p>(4) require all users of the Heliport to co-operate in the programme to promote safety at, and the safe use of the heliport by immediately informing it of any accidents, incidents, defects and faults which have bearing on safety;</p> <p>(5) keep under review its safety management system and take such corrective action as is necessary to ensure that it operates properly.</p>			
12.1.4.5	<p>HELIPORT OPERATOR'S INTERNAL SAFETY AUDIT/REPORTING</p> <p>(1) Implement a Safety management system acceptable to the Authority as prescribed in Nig. CARs Part 20.</p>			



STATEMENT OF COMPLIANCE

	<ul style="list-style-type: none"> (a) The heliport operator shall arrange for an audit of the safety management system, including inspection of the heliport facilities and equipment; (b) The audits referred to in paragraph 12.1.4.5(a) above shall be carried out every 12 months, or less as agreed with the Authority; (c) The heliport operator shall ensure that the audit reports, including the report on the heliport facilities, services and equipment are prepared by suitably qualified safety personnel; (d) The heliport operator shall retain a copy of the report(s) referred to in paragraph 12.1.4.5 (c) above for a period to be agreed with the Authority. The Authority may request a copy of the report(s) for its review and reference; (e) The report(s) referred to in paragraph 12.1.4.5 (c) above shall be prepared and signed by the persons who carried out the audits and inspections. 			
12.1.4.6	<p>ACCESS TO THE HELIPORT.</p> <ul style="list-style-type: none"> (a) The applicant for or holder of heliport certificate shall: <ul style="list-style-type: none"> (1) allow access by authorized officers of the Authority to inspect and test the heliport facilities, services and equipment, inspect the heliport operator's document and records in order to meet its continuing surveillance obligation and ensure safety of heliport operations. (2) allow access of personnel so authorized by the Authority to carry out pre-destination inspection, audit and test of the Heliport facilities, services and equipment, inspect the Heliport operator's document and records of a helideck on a moveable rig or ship prior to arrival of such vessel into the territorial waters 			



STATEMENT OF COMPLIANCE

	<p>of Nigeria from the country of shipment in order to ensure safety of heliport operations</p> <p>(3) co-operate in conducting the activities referred to in paragraph (a) and (b) above.</p>			
12.1.4.7	<p>HELIPORT INSPECTION.</p> <p>The heliport operator shall inspect the heliport daily and as circumstances require to ensure aviation safety.</p>			
12.1.4.8	<p>REMOVAL OF OBSTRUCTIONS FROM THE HELIPORT SURFACE.</p> <p>The heliport operator shall:</p> <p>(a) establish the obstacle limitation surfaces and meet the requirements for the surfaces and any obstacles that may affect them, as set out for heliports in the applicable heliport Regulation.</p> <p>(b) remove from the heliport surface any obstruction that is likely to be hazardous to helicopter operation.</p> <p>(c) notify the Authority prior to commencement of construction or alteration works.</p> <p>(d) monitor and report to the Authority any erection of obstacles within the obstacle limitation surfaces to ensure the safety of airspace for helicopter operations.</p>			
12.1.4.9	<p>PUBLIC PROTECTION AND HELIPORT SECURITY.</p> <p>(a) The heliport operator shall:</p> <p>(1) provide public protection and heliport security in accordance with Part 17 of these Regulations ;</p> <p>(2) provide perimeter fence, road, barriers and doors with controlled access to prevent inadvertent and unauthorized entry of animals and human beings and where necessary provide security lighting on the perimeter fence ;</p> <p>(3) affix signs and prohibition notices at the perimeter of security areas within the heliport.</p>			



STATEMENT OF COMPLIANCE

12.1.4.10	<p>HELIPORT DATA (a) The heliport operator shall ensure the accuracy of the determination and reporting of heliport related aeronautical data with emphasis on the following areas: (1) Adherence to accuracy and integrity requirements set forth in these regulations; (2) Maintenance of integrity of aeronautical data and avoidance of corruption of data at all times; (3) Ensuring that data are measured or described as appropriate and should cover heliport reference point, elevation, final approach and take-off area (FATO), touchdown and lift-off area (TLOF) and declared distances and other required data as specified in these regulations.</p>			
12.1.4.11	<p>NOTIFYING AND REPORTING. (a) The heliport operator shall adhere to the requirement to notify and report appropriately to the Authority, the air traffic service provider and pilots any condition that may affect aviation safety, within the specified time limits required by these Regulations.</p>			
12.1.4.12	<p>PHYSICAL CHARACTERISTICS. (a) The heliport operator shall provide at least one Final Approach And Take-Off Area (FATO), one Touchdown And Lift-Off Area (TLOF), helicopter clearway where necessary, safety areas, helicopter ground taxiways, air taxiways, air transit routes and apron with particular attention to the following: (1) class of helicopters the heliport can serve; (2) Local conditions such as elevation, temperature and visual or instrument meteorological conditions; and (3) The heliport data, physical characteristics, obstacle limitation surfaces, visual aids, equipment and installations provided at the heliport shall comply with the appropriate heliport design requirements as prescribed in the applicable heliport standard Subpart 2 of this Volume.</p>			



STATEMENT OF COMPLIANCE

12.1.4.13	<p>VISUAL AIDS The heliport operator shall provide and maintain at least one wind direction indicator, markings and markers including heliport identification marking, heliport beacon, heliport light including approach lighting and heliport identification (H) lightings where desirable and practicable, obstacle protection surface (HAPI and PAPI), aiming point lights, taxiway lights and floodlighting of obstacles in accordance with the requirements specified in the applicable heliport standard.</p>			
12.1.4.14	<p>RESCUE AND FIRE FIGHTING AT HELIPORTS. The heliport operator shall: (a) determine the level of protection to be provided for rescue and firefighting based on the over-all size of the largest helicopter that uses the heliport in accordance with these regulations; (b) provide principal extinguishing agents (foam compound) meeting the minimum performance level B; (c) provide complimentary agents preferably dry chemical powder and halons; (d) provide vehicles with a discharge rate of foam compound as prescribed in these regulations; (e) provide rescue equipment commensurate with the level of helicopter operations; (f) equip the firefighting unit with trained personnel, vehicle and equipment to achieve a response time not exceeding two minutes in optimum conditions of visibility and surface conditions; (g) provide rescue and firefighting services as prescribed in the applicable heliport standard.</p>			
12.1.4.15	<p>HELIPORT EMERGENCY MANAGEMENT SYSTEMS. The heliport operator shall: (a) establish procedures to ensure that all participants in any heliport</p>			



STATEMENT OF COMPLIANCE

	<p>emergency with allocated duties are familiar with and are properly trained for their assignments;</p> <p>(b) test the effectiveness of the emergency management system through periodic exercise including a full-scale heliport emergency exercise annually;</p> <p>(c) correct any deficiencies identified during any full-scale exercise and review his or her system with the aim of achieving improved efficiency and safety.</p>			
12.1.4.16	<p>AERONAUTICAL STUDIES. The Heliport operator shall carry out aeronautical studies where necessary under the conditions, procedures and technical guidelines given in these regulations.</p>			
12.1.4.17	<p>PASSENGER BRIEFING ROOM The heliport operator shall provide a briefing room for safety briefing.</p>			
	<p>SUB-PART 2 HELIPORT DESIGN AND OPERATIONS</p>			
12.2.1	<p>GENERAL</p>			
12.2.1.1	<p>INTRODUCTION</p> <p>Introductory Note — this subpart contains Requirements that Prescribe the physical characteristics and obstacle limitation surfaces to be provided for at heliports, and certain facilities and technical services normally provided at a heliport. It is not intended that these specifications limit or regulate the operation of an aircraft.</p> <p>The specifications in this subpart modify or complement those in previous subparts which, where appropriate, are also applicable to heliports. Where a particular issue is subject of specification in this subpart that specification will supersede any other specification on that</p>			



STATEMENT OF COMPLIANCE

	<p>particular issue in previous subpart. Throughout this subpart the term “heliport” is used; however, it is intended that these specifications also apply to areas for the exclusive use of helicopters at an aerodrome primarily meant for the use of aeroplanes.</p> <p>When designing a heliport, the critical design helicopter, having the largest set of dimensions and the greatest maximum take-off mass (MTOM) the heliport is intended to serve, would need to be considered. It is to be noted that provisions for helicopter flight operations are contained in ICAO Annex 6, Part III.</p>			
<p>12.2.1.2</p>	<p>APPLICABILITY</p> <p><i>Note — the dimensions discussed in Subpart 1 are based on consideration of singlemain- rotor helicopters. For tandem-rotor helicopters the heliport design will be based on a case-by-case review of the specific models using the basic requirement for a safety area and protection areas specified in this Subpart. The specifications of the main chapters of this subpart are applicable for visual heliports that may or may not incorporate the use of a Point-in-space approach or departure. The specifications of this subpart are not applicable for water heliports (touchdown or lift-off on the surface of the water).</i></p> <p>(a) The interpretation of some of the specifications here expressly requires the exercising of discretion, the taking of a decision or the performance of a function by the heliport operator. In other specifications, the expression appropriate authority does not actually appear although its inclusion is implied. In both cases, the responsibility for whatever determination or action necessary shall rest with the Nigeria Civil Aviation Authority (NCAA).</p> <p>(b) The specifications in this subpart shall apply to all heliports intended to be used by helicopters in civil aviation. The specifications of subpart 1 shall apply, where appropriate, to these heliports as well.</p>			



STATEMENT OF COMPLIANCE

	<p>(c) Wherever a colour is referred to in this section, the specifications for that colour earlier given shall apply Nig.CARs Part 12 vol 1, IS 12.2.1.2.</p>			
12.2.1.3	<p>COMMON REFERENCE SYSTEMS</p> <p>(a) HORIZONTAL REFERENCE SYSTEM</p> <p>(1) World Geodetic System — 1984 (WGS-84) shall be used as the horizontal (geodetic) reference system. Reported aeronautical geographical coordinates (indicating latitude and longitude) shall be expressed in terms of the WGS-84 geodetic reference datum.</p> <p><i>Note. — Comprehensive guidance material concerning WGS-84 is contained in the World Geodetic System — 1984(WGS-84) Manual (Doc 9674).</i></p> <p>(b) VERTICAL REFERENCE SYSTEM.</p> <p>(1) Mean sea level (MSL) datum, which gives the relationship of gravity related height (elevation) to a surface known as the geoid, shall be used as the vertical reference system.</p> <p><i>Note1. — The geoid globally most closely approximates MSL. It is defined as the equipotential surface in the gravity field of the Earth which coincides with the undisturbed MSL extended continuously through the continents.</i></p> <p><i>Note2. — Gravity-related heights (elevations) are also Referred to as orthometric heights while distances of points above the ellipsoid are referred to as ellipsoidal heights.</i></p> <p>(c) TEMPORAL REFERENCE SYSTEM</p> <p>(1) The Gregorian calendar and Coordinated Universal Time (UTC) shall be used as the temporal reference system.</p>			



STATEMENT OF COMPLIANCE

	(2) When a different temporal reference system is used, this shall be indicated in GEN 2.1.2 of the Aeronautical Information Publication (AIP).			
12.2.2	HELIPORT DATA			
12.2.2.1	<p>AERONAUTICAL DATA</p> <p>(a) Determination and reporting of heliport related aeronautical data shall be in accordance with the accuracy and integrity classification required to meet the needs of the end-user of aeronautical data.</p> <p><i>Note - Specifications concerning the accuracy and integrity classification related to heliport related aeronautical data are contained in PANS-AIM (Doc 10066), Appendix 1</i></p> <p>(b) Digital data error detection techniques shall be used during the transmission and/or storage of aeronautical data and digital data sets.</p> <p><i>Note. — Detailed specifications concerning digital data error (a) detection techniques are contained in PANS-AIM (Doc 10066).</i></p>			
12.2.2.2	<p>HELIPORT REFERENCE POINT</p> <p>(a) A heliport reference point shall be established for a heliport not co-located with an aerodrome.</p> <p><i>Note.— When the heliport is co-located with an aerodrome ,the established aerodrome reference point serves both aerodrome and heliport .</i></p> <p>(b) The heliport reference point shall be located near the initial or planned geometric centre of the heliport and shall normally remain where first established.</p>			



STATEMENT OF COMPLIANCE

	(c) The position of the heliport reference point shall be measured and reported to the Aeronautical Information Services in degrees, minutes and seconds.			
12.2.2.3	<p>HELIPORT ELEVATIONS</p> <p>(a) The heliport elevation and geoid undulation at the heliport elevation position shall be measured and reported to the Aeronautical Information Services to the accuracy of one-half metre or foot.</p> <p>(b) The elevation of the touchdown and lift-off area and/or the elevation and geoid undulation of each threshold of the final approach and take-off area (where appropriate) shall be measured and reported to the Aeronautical Information Services to the accuracy of one half metre or foot:</p> <p><i>Note.— Geoid undulation must be measured in accordance with the appropriate system of coordinates.</i></p>			
12.2.2.4	<p>HELIPORT DIMENSIONS AND RELATED INFORMATION</p> <p>(a) The following data shall be measured or described, as appropriate, for each facility provided on a heliport:</p> <p>(1) heliport type — surface-level, elevated, shipboard or helideck;</p> <p>(2) touchdown and lift-off area — dimensions to the nearest metre or foot, slope, surface type, bearing strength in tonnes (1000 kg);</p> <p>(3) FATO — type of FATO, true bearing to one-hundredth of a degree, designation number (where appropriate), length, and width to the nearest meter or foot, slope, surface type;</p> <p>(4) safety area — length, width and surface type;</p>			



STATEMENT OF COMPLIANCE

	<p>(5) helicopter taxiway – and helicopter, taxi route— designation, width, surface type;</p> <p>(6) apron — surface type, helicopter stands;</p> <p>(7) clearway — length, ground profile and ;</p> <p>(8) visual aids for approach procedures, marking and lighting of FATO, helicopter ground taxiways, helicopter air taxiway, and helicopter stands</p> <p>(b) The geographical coordinates of the geometric centre of the touchdown and lift-off area and/or of each threshold of the final approach and take-off area (where appropriate) shall be measured and reported to the Aeronautical Information Services in degrees, minutes, seconds and hundredths of seconds.</p> <p>(c) The geographical coordinates of appropriate centre line points of helicopter taxiways and helicopter taxi routes shall be measured and reported to the Aeronautical Information Services in degrees, minutes, seconds and hundredths of seconds.</p> <p>(d) The geographical coordinates of each helicopter stand shall be measured and reported to the Aeronautical Information Services in degrees, minutes, seconds and hundredths of seconds.</p> <p>(e) The geographical coordinates of obstacles in Area 2 (the part within the heliport boundary) and in Area 3 shall be measured and reported to the aeronautical information services in degrees, minutes, seconds and tenths of seconds. In addition, the top elevation, type, marking and lighting (if any) of obstacles shall be reported to the Aeronautical Information Services.</p> <p><i>Note .— PANS-AIM (Doc 10066), ICAO Annex 14 Vol. II Appendix 8 provides requirements for obstacle data determination in Areas 2 and 3</i></p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

12.2.2.5	<p>DECLARED DISTANCES</p> <p>(a) The following distances to the nearest metre or foot shall be declared, where relevant, for a heliport:</p> <p>(1) take-off distance available; (2) rejected take-off distance available; and (3) landing distance available.</p>			
12.2.2.6	<p>COORDINATION BETWEEN AERONAUTICAL INFORMATION SERVICES AND HELIPORT AUTHORITIES</p> <p>(a) To ensure that Aeronautical Information Services units obtain information to enable them to provide up-to-date pre-flight information and to meet the need for in-flight information, arrangements shall be made between Aeronautical Information Services and Heliport Authorities responsible for Heliport Services to report to the responsible Aeronautical Information Services, with a minimum of delay:</p> <p>(1) information on heliport conditions;</p> <p>(2) the operational status of associated facilities, services and navigation aids within their area of responsibility;</p> <p>(3) any other information considered to be of operational significance.</p> <p>(b) Before introducing changes to the air navigation system, due account shall be taken by the services responsible for such changes of the time needed by the Aeronautical Information Services for the preparation, production and issue of relevant material for promulgation. To ensure timely provision of the information to the Aeronautical Information Services, close co-ordination between those services concerned is therefore required.</p> <p>(c) Of a particular importance are changes to aeronautical information that affect charts and/or computer based navigation</p>			



STATEMENT OF COMPLIANCE

	<p>systems which qualify to be notified by the Aeronautical Information Regulation and Control (AIRAC) system as specified in ICAO Annex 15 Chapter 6. The predetermined, internationally agreed AIRAC effective dates shall be observed by the responsible Heliport Services when submitting the raw information/data to Aeronautical Information Services.</p> <p><i>Note.— Detailed specifications concerning the AIRAC system are contained in ICAO PANS-AIM (Doc 10066), Chapter</i></p> <p>(d) The heliport services responsible for the provision of raw aeronautical information/data to the Aeronautical Information Services shall do that while taking into account accuracy and integrity requirements required to meet the needs of the end-user of aeronautical data</p> <p><i>Note 1.— Specifications concerning the accuracy and integrity classification of heliport-related aeronautical data are contained in ICAO PANS-AIM (Doc 10066), Appendix 1.</i></p> <p><i>Note 2 — Specifications for the issue of a NOTAM are contained in ICAO Annex 15, Chapter 6, and PANS-AIM (Doc 10066), Appendices 3 and 4 respectively.</i></p> <p><i>Note 3 — The AIRAC information is distributed by the AIS at least 42 days in advance of the AIRAC effective dates with the objective of reaching recipients at least 28 days in advance of the effective date.</i></p> <p><i>Note 4 — The schedule of the predetermined internationally agreed AIRAC common effective dates at intervals of 28 days, including 19 November 1997 and guidance for the AIRAC use are contained in the Aeronautical Information Services Manual (Doc 8126, Chapter 2, 14.IV.2.6).</i></p>			
12.2.2.7	<p>RESCUE AND FIREFIGHTING</p> <p><i>Note.— See 12.2.6.2 for information on rescue and firefighting services.</i></p>			



STATEMENT OF COMPLIANCE

	<p>(a) Information concerning the level of protection provided at a heliport for helicopter rescue</p> <p>(b) The level of protection normally available at a heliport shall be expressed in terms of the category of the rescue and firefighting service as described in 12.2.6.2 and in accordance with the types and amounts of extinguishing agents normally available at the heliport.</p> <p>(c) Changes in the level of protection normally available at a heliport for rescue and firefighting shall be notified to the appropriate aeronautical information services units and, where applicable, air traffic units to enable them to provide the necessary information to arriving and departing helicopters. When such a change has been corrected, the above units shall be advised accordingly.</p> <p><i>Note. — Changes in the level of protection from that normally available at the heliport could result from, but may not be limited to, a change in the availability of extinguishing agent or equipment used to deliver agents, or of personnel used to operate the equipment.</i></p> <p>(d) A change shall be expressed in terms of the new category of the rescue and firefighting service available at the heliport.</p>			
<p>12.2.3</p>	<p>PHYSICAL CHARACTERISTICS</p>			
<p>12.2.3.1</p>	<p>ONSHORE HELIPORTS</p> <p><i>Note 1.— The provisions given in this section are based on the design assumption that no more than one helicopter will be in the FATO at the same time.</i></p> <p><i>Note 2.— The design provisions given in this section assume when conducting operations to a FATO in proximity to another FATO, these operations will not be simultaneous. If simultaneous helicopter operations are required, appropriate separation distances between</i></p>			



STATEMENT OF COMPLIANCE

FATOs need to be determined, giving due regard to such issues as rotor downwash and airspace, and ensuring the flight paths for each FATO, defined in Chapter 4, do not overlap. Further guidance on this issue is given in the Heliport Manual (Doc 9261).

Note 3.— The provisions given in this section are common for surface-level heliports and elevated heliports unless otherwise specified.

Note 4.— Guidance on the minimum size for elevated FATO/TLOF in order to permit facilitation of essential operations around the helicopter is given in the Heliport Manual (Doc 9261).

Note 5.— Guidance on structural design to account for the presence on elevated heliports of personnel, snow, freight, and refuelling and firefighting equipment, etc. is given in the Heliport Manual (Doc 9261).

Note 6.— Guidance on siting of a heliport and the location of the various defined areas, with due consideration of the effects of rotor downwash and other aspects of helicopter operations on third parties, is given in the Heliport Manual (Doc 9261).

FINAL APPROACH AND TAKE-OFF AREA (FATO)

Note. — Guidance on siting and orientation of the FATO at a heliport to minimize interference of arrival and departure tracks with areas approved for residential use and other noise-sensitive areas close to the heliport is given in the Heliport Manual (Doc 9261).

- (a) A FATO shall:
 - (1) provide:
 - (i) an area free of obstacles, except for essential objects which because of their function are located on it, and of sufficient size and shape to ensure containment of every part of the design helicopter in the final phase of approach and commencement of take-off in accordance with the intended procedures;



STATEMENT OF COMPLIANCE

	<p><i>Note.— Essential objects are visual aids (e.g. lighting) or others (e.g. firefighting systems) necessary for safety purposes. For further requirements regarding penetration of a FATO by essential objects, see 12.2.3(a)(4)</i></p> <ul style="list-style-type: none">(ii) when solid, a surface which is resistant to the effects of rotor downwash; and(A) when collocated with a TLOF, is contiguous and flush with the TLOF, has bearing strength capable of withstanding the intended loads and ensures effective drainage; or(B) when not collocated with a TLOF, is free of hazards should a forced landing be required; <p><i>Note.— Resistant implies that effects from rotor downwash neither cause a degradation of the surface nor result in flying debris. And</i></p> <ul style="list-style-type: none">(2) be associated with a safety area.(b) A heliport shall be provided with at least one FATO, which need not be solid. <p><i>Note.— A FATO may be located on or near a runway strip or taxiway strip.</i></p> <ul style="list-style-type: none">(c) The minimum dimensions of a FATO shall be:<ul style="list-style-type: none">(1) where intended to be used by helicopters operated in performance class 1:<ul style="list-style-type: none">(i) the length of the rejected take-off distance (RTOD) for the required take-off procedure prescribed in the helicopter flight manual (HFM) of the helicopters for which the FATO is intended, or 1.5 Design D, whichever is greater; and			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>(ii) the width for the required procedure prescribed in the HFM of the helicopters for which the FATO is intended, or 1.5 Design D, whichever is greater; and</p> <p>(2) where intended to be used by helicopters operated in performance class 2 or 3, the lesser of:</p> <p>(i) an area within which can be drawn a circle of diameter of 1.5 Design D; or</p> <p>(ii) when there is a limitation on the direction of approach and touchdown, an area of sufficient width to meet the requirement of 12.2.3.1(a)(1)(i) but not less than 1.5 times the overall width of the design helicopter.</p> <p><i>Note 1.— The RTOD is intended to ensure containment of the helicopter during a rejected take-off. Although some HFMs provide the RTOD, in others the dimension provided is the “minimum demonstrated ... size” (where “...” could be “heliport”, “runway”, “helideck”, etc. and this may not include helicopter containment. When this is the case, it is necessary to consider sufficient safety area dimensions as well as the dimensions of 1.5•D for the FATO, should the HFM not deliver data. For further guidance see the Heliport Manual (Doc 9261).</i></p> <p><i>Note 2.— Local conditions, such as elevation, temperature and permitted manoeuvring may need to be considered when determining the size of a FATO. Guidance is given in the Heliport Manual (Doc 9261)</i></p> <p>(d) Essential objects located in a FATO shall not penetrate a horizontal plane at the FATO elevation by more than 5 cm.</p> <p>(e) Intentionally left blank</p> <p>(f) Intentionally left blank</p> <p>(g) A FATO shall be surrounded by a safety area which need not be solid.</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>SAFETY AREAS</p> <p>(h) A safety area shall provide:</p> <ul style="list-style-type: none">(1) an area free of obstacles, except for essential objects which because of their function are located on it, to compensate for manoeuvring errors; and(2) when solid, a surface which is contiguous and flush with the FATO, is resistant to the effects of rotor downwash and ensures effective drainage. <p>(i) The safety area surrounding a FATO shall extend outwards from the periphery of the FATO for a distance of at least 3 m or 0.25 Design D, whichever is greater (see Figure 3-1).</p> <p>(j) No mobile object shall be permitted in a safety area during helicopter operations.</p> <p>(k) Essential objects located in the safety area shall not penetrate a surface originating at the edge of the FATO at a height of 25 cm above the plane of the FATO sloping upwards and outwards at a gradient of 5 per cent.</p> <p>(l) Intentionally left blank</p> <p>PROTECTED SIDE SLOPE</p> <p>(m) A heliport shall be provided with at least one protected side slope, rising at 45 degrees from the edge of the safety area and extending to a distance of 10 m (see Figure 3-2).</p> <p>(n) Intentionally left blank</p> <p>(o) The surface of a protected side slope shall not be penetrated by obstacles.</p> <p>(p) A helicopter clearway shall provide:</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>(i) an area free of obstacles, except for essential objects which because of their function are located on it, and of sufficient size and shape to ensure containment of the design helicopter when it is accelerating in level flight, and close to the surface, to achieve its safe climbing speed; and</p> <p>(ii) when solid, a surface which is contiguous and flush with the FATO, is resistant to the effects of rotor downwash and is free of hazards should a forced landing be required.</p> <p>(q) When a helicopter clearway is provided, it shall be located beyond the end of the FATO.</p> <p>(r) Intentionally left blank</p> <p>(s) Intentionally left blank</p> <p>(t) Intentionally left blank</p> <p>TOUCHDOWN AND LIFT-OFF AREA (TLOF) <i>Note.— The inclusion of detailed specifications for helicopter clearways in this section is not intended to imply that a clearway has to be provided.</i></p> <p>(u) A TLOF shall:</p> <p>(1) provide:</p> <p>(i) an area free of obstacles and of sufficient size and shape to ensure containment of the undercarriage of the most demanding helicopter the TLOF is intended to serve in accordance with the intended orientation;</p> <p>(ii) a surface which:</p> <p>(A) has sufficient bearing strength to accommodate the dynamic loads associated with the anticipated type of arrival of the helicopter at the designated TLOF;</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>(B) is free of irregularities that would adversely affect the touchdown or lift-off of helicopters;</p> <p>(C) has sufficient friction to avoid skidding of helicopters or slipping of persons; and</p> <p>(D) is resistant to the effects of rotor downwash;</p> <p>(E) ensures effective drainage while having no adverse effect on the control or stability of a helicopter during touchdown and lift-off, or when stationary; and</p> <p>(2) be associated with a FATO or a stand.</p> <p>(v) A heliport shall be provided with at least one TLOF.</p> <p>(w) A TLOF shall be provided whenever it is intended that the undercarriage of the helicopter will touch down within a FATO or stand, or lift off from a FATO or stand.</p> <p>(x) The minimum dimensions of a TLOF shall be:</p> <p>(1) when in a FATO intended to be used by helicopters operated in performance class 1, the dimensions for the required procedure prescribed in the Helicopter Flight Manuals of the helicopters for which the TLOF is intended; and</p> <p>(2) when in a FATO intended to be used by helicopters operated in performance class 2 or 3, or in a stand:</p> <p>(i) when there is no limitation on the direction of touchdown, of sufficient size to contain a circle of diameter of at least 0.83 D of:</p> <p>(A) in a FATO, the design helicopter; or</p> <p>(B) in a stand, the largest helicopter the stand is intended to serve; and</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>(ii) when there is a limitation on the direction of touchdown, of sufficient width to meet the requirement of 12.2.3.1(u)(1)(i) but not less than twice the undercarriage width (UCW) of:</p> <p>(A) in a FATO, the design helicopter; or</p> <p>(B) in a stand, the most demanding helicopter the stand is intended to serve.</p> <p>(y) For an elevated heliport, the minimum dimensions of a TLOF, when in a FATO, shall be of sufficient size to contain a circle of diameter of at least 1 Design D.</p> <p>(z) Intentionally left blank</p> <p>(aa) Intentionally left blank</p> <p>(ab) When a TLOF is within a helicopter stand, it shall be centered on the stand.</p> <p>(ac) A TLOF shall be provided with markings which clearly indicate the touchdown position and, by their form, any limitations on maneuvering.</p> <p><i>Note.— When a TLOF in a FATO is larger than the minimum dimensions, the touchdown/positioning marking (TDPM) may be offset while ensuring containment of the undercarriage within the TLOF and the helicopter within the FATO.</i></p> <p>(ad) Intentionally left blank (ae) Intentionally left blank</p> <p>(af) Safety devices such as safety nets or safety shelves shall be located around the edge of an elevated heliport but shall not exceed the height of the TLOF.</p> <p>HELICOPTER TAXIWAYS AND TAXI-ROUTES</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

Note 1.— The specifications for ground taxi-routes and air taxi-routes are intended for the safety of simultaneous operations during the manoeuvring of helicopters. The effect of wind velocity/turbulence induced by rotor downwash would need to be considered.

Note 2.— The defined areas addressed in this section are:

- a) taxiways associated with air taxi-routes which may be used by both wheeled and skidded helicopters for either ground or air taxiing;
- b) ground taxi-routes which are meant for use by wheeled helicopters for ground taxiing only; and
- c) air taxi-routes which are meant for use by air taxiing only.

HELICOPTER TAXIWAYS

Note 1.— A helicopter taxiway is intended to permit the surface movement of a wheeled helicopter under its own power.

Note 2.— A helicopter taxiway may be used by a wheeled helicopter for air taxi if associated with a helicopter air taxi- route.

Note 3.— When a taxiway is intended for use by aeroplanes and helicopters, the provisions for aeroplane taxiways, taxiway strips, helicopter taxiways and taxi-routes will be taken into consideration and the more stringent requirements will be applied.

(ag) A helicopter taxiway shall:

- (1) provide:
 - (i) an area free of obstacles and of sufficient width to ensure containment of the undercarriage of the most demanding wheeled helicopter the taxiway is intended to serve;
 - (ii) a surface which:



STATEMENT OF COMPLIANCE

	<p>(A) has bearing strength to accommodate the taxiing loads of the helicopters the taxiway is intended to serve;</p> <p>(B) is free of irregularities that would adversely affect the ground taxiing of helicopters; and</p> <p>(C) is resistant to the effects of rotor downwash;</p> <p>(D) ensured effective drainage while having no adverse effect on the control or stability of a wheeled helicopter when being manoeuvred under its own power, or when stationary; and</p> <p>(2) be associated with a taxi-route.</p> <p>(ah) The minimum width of a helicopter taxiway shall be the lesser of:</p> <p>(1) twice the UCW of the most demanding helicopter the taxiway is intended to serve; or</p> <p>(2) a width meeting the requirements of 12.2.3.1(ag)(1)(i).</p> <p>(ai) Intentionally left blank</p> <p>HELICOPTER TAXI-ROUTES</p> <p>(aj) A helicopter taxi-route shall provide:</p> <p>(1) an area free of obstacles, except for essential objects which because of their function are located on it, established for the movement of helicopters; of sufficient width to ensure containment of the largest helicopter the taxi-route is intended to serve; and</p> <p>(2) when solid, a surface which is resistant to the effects of rotor downwash; and</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>(i) when collocated with a taxiway:</p> <p>(A) is contiguous and flush with the taxiway;</p> <p>(B) does not present a hazard to operations; and</p> <p>(C) ensures effective drainage; and</p> <p>(ii) when not collocated with a taxiway, is free of hazards should a forced landing be required.</p> <p>(ak) No mobile object shall be permitted on a taxi-route during helicopter operations.</p> <p><i>Note.— See the Heliport Manual (Doc 9261) for further guidance.</i></p> <p>(al) Intentionally left blank</p> <p>HELICOPTER GROUND TAXI-ROUTES</p> <p>(am) A helicopter ground taxi-route shall have a minimum width of 1.5 times the overall width of the largest helicopter it is intended to serve, and be centered on a taxiway. (See Figure 3-3.)</p> <p>HELICOPTER AIR TAXI-ROUTES</p> <p><i>Note.— A helicopter air-taxi route is intended to permit the movement of a helicopter above the surface at a height normally associated with ground effect and at ground speed less than 37 km/h (20 kt).</i></p> <p>(ao) A helicopter air taxi-route shall have a minimum width of twice the overall width of the largest helicopter it is intended to serve.</p> <p>(ap) If collocated with a taxiway for the purpose of permitting both ground and air taxi operations (see Figure 3-4):</p> <p>(1) the helicopter air taxi-route shall be centred on the taxiway; and</p> <p>(2) essential objects located in the helicopter air taxi-route shall not:</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>(i) be located at a distance of less than 50 cm outwards from the edge of the helicopter taxiway; and</p> <p>(ii) penetrate a surface originating 50 cm outwards of the edge of the helicopter taxiway and a height of 25 cm above the surface of the taxiway and sloping upwards and outwards at a gradient of 5 per cent.</p> <p>(ar) A helicopter stand shall:</p> <p>(1) provide:</p> <p>(i) an area free of obstacles and of sufficient size and shape to ensure containment of every part of the largest helicopter the stand is intended to serve when it is being positioned within the stand;</p> <p>(ii) a surface which:</p> <p>(A) is resistant to the effects of rotor downwash;</p> <p>(B) is free of irregularities that would adversely affect the maneuvering of helicopters;</p> <p>(C) has bearing strength capable of withstanding the intended loads;</p> <p>(D) has sufficient friction to avoid skidding of helicopters or slipping of persons; and</p> <p>(E) ensures effective drainage while having no adverse effect on the control or stability of a wheeled helicopter when being maneuvered under its own power, or when stationary; and</p> <p>(2) be associated with a protection area.</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>(as) The minimum dimensions of a helicopter stand shall be:</p> <ul style="list-style-type: none"> (1) a circle of diameter of 1.2 D of the largest helicopter the stand is intended to serve; or (2) when there is a limitation on maneuvering and positioning, of sufficient width to meet the requirement of 12.2.3.1(ar)(1)(i) but not less 1.2 times overall width of largest helicopter the stand is intended to serve. <p><i>Note 1.— For a helicopter stand intended to be used for taxi-through only, a width less than 1.2 D but which provides containment and still permits all required functions of a stand to be performed, might be used (in accordance with 12.2.3.1(ar)(1)(i))</i></p> <p><i>Note 2.— For a helicopter stand intended to be used for turning on the ground, the minimum dimensions may be influenced by the turning circle data provided by the manufacturer and are likely to exceed 1.2 D. See the Heliport Manual (Doc 9261) for further guidance.</i></p> <p>(at) Intentionally left blank</p> <p>(au) Each helicopter stand shall be provided with positioning markings to clearly indicate where the helicopter is to be positioned and, by their form, any limitations on maneuvering.</p> <p>(av) A stand shall be surrounded by a protection area which need not be solid.</p> <p>PROTECTION AREAS</p> <p>(aw) A protection area shall provide:</p> <ul style="list-style-type: none"> (1) an area free of obstacles, except for essential objects which because of their function are located on it; and 			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>(2) when solid, a surface which is contiguous and flush with the stand, is resistant to the effects of rotor downwash and ensures effective drainage.</p> <p>(ax) When associated with a stand designed for turning, the protection area shall extend outwards from the periphery of the stand for a distance of 0.4 D (see Figure 3.5).</p> <p>(ay) When associated with a stand designed for taxi-through, the minimum width of the stand and protection area shall not be less than the width of the associated taxi-route (see Figures 3.6 and 3.7).</p> <p>(az) When associated with a stand designed for non-simultaneous use (see Figures 3.8 and 3.9):</p> <ul style="list-style-type: none"> (1) the protection area of adjacent stands may overlap but shall not be less than the required protection area for the larger of the adjacent stands; and (2) the adjacent non-active stand may contain a static object but it shall be wholly within the boundary of the stand. <p><i>Note.— To ensure that only one of the adjacent stands is active at a time, instruction to pilots in the AIP make clear that a limitation on the use of the stands is in force.</i></p> <p>(ba) No mobile object shall be permitted in a protection area during helicopter operations.</p> <p>(bb) Essential objects located in the protection area shall not:</p> <ul style="list-style-type: none"> (1) if located at a distance of less than 0.75 D from the centre of the helicopter stand, penetrate a surface at a height of 5 cm above the surface of the central zone; and (2) if located at a distance of 0.75 D or more from the centre of the helicopter stand, penetrate a surface at a height of 25 cm above 			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>the plane of the central zone and sloping upwards and outwards at a gradient of 5 per cent.</p> <p>(bc) Intentionally left blank</p> <p>LOCATION OF A FATO IN RELATION TO A RUNWAY OR TAXIWAY</p> <p>(bd) Where a FATO is located near a runway or taxiway, and where simultaneous operations are planned, the separation distance between the edge of a runway or taxiway and the edge of a FATO shall not be less than the appropriate dimension in Table 3-1.</p> <p>(be) Intentionally left blank</p>			
12.2.3.2	<p>HELIDECKS</p> <p><i>Note.— The following specifications are for helidecks located on structures engaged in such activities as mineral exploitation, research or construction. See 12.2.3.4 for shipboard heliport provisions.</i></p> <p>FATOs AND TLOFs</p> <p><i>Note 1.— For helidecks that have a 1 D or larger FATO it is presumed that the FATO and the TLOF will always occupy the same space and have the same load bearing characteristics so as to be coincidental. For helidecks that are less than 1 D, the reduction in size is only applied to the TLOF which is a load bearing area. In this case, the FATO remains at 1 D but the portion extending beyond the TLOF perimeter need not be load bearing for helicopters. The TLOF and the FATO may be assumed to be collocated.</i></p> <p><i>Note 2.— Guidance on the effects of airflow direction and turbulence, prevailing wind velocity and high temperatures from gas turbine exhausts or flare-radiated heat on the location of the FATO is given in the Heliport Manual (Doc 9261).</i></p> <p><i>Note 3.— Guidance on the design and markings for helideck parking areas is given in the Heliport Manual (Doc 9261).</i></p>			



STATEMENT OF COMPLIANCE

	<p>(a) The specifications in paragraphs 12.2.3.3(n) and 12.2.3.3(o) shall be applicable for helidecks completed on or after 1 January 2012.</p> <p>(b) A helideck shall be provided with one FATO and one coincident or collocated TLOF.</p> <p>(c) A FATO may be any shape but shall be of sufficient size to contain an area within which can be accommodated a circle of diameter of not less than 1 D of the largest helicopter the helideck is intended to serve.</p> <p>(d) A TLOF may be any shape but shall be of sufficient size to contain:</p> <ol style="list-style-type: none"> (1) for helicopters with an MTOM of more than 3 175 kg, an area within which can be accommodated a circle of diameter not less than 1 D of the largest helicopter the helideck is intended to serve; and (2) for helicopters with an MTOM of 3 175 kg or less, an area within which can be accommodated a circle of diameter not less than 0.83 D of the largest helicopter the helideck is intended to serve. <p>(e) Intentionally left blank</p> <p>(f) A helideck shall be arranged to ensure that a sufficient and unobstructed air-gap is provided which encompasses the full dimensions of the FATO.</p> <p><i>Note.— Specific guidance on the characteristics of an air-gap is given in the Heliport Manual (Doc 9261). As a general rule, except for shallow superstructures of three stories or less, a sufficient air-gap will be at least 3 m.</i></p> <p>(g) The FATO should be located so as to avoid, as far as is practicable, the influence of environmental effects, including turbulence, over the FATO which could have an adverse impact on helicopter operations.</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>(h) The TLOF shall be dynamic load-bearing.</p> <p>(i) The TLOF shall provide ground effect.</p> <p>(j) No fixed object shall be permitted around the edge of the TLOF except for frangible objects, which, because of their function, must be located thereon.</p> <p>(k) For any TLOF 1 D or greater and any TLOF designed for use by helicopters having a D-value of greater than 16.0 m, objects installed in the obstaclefree sector whose function requires them to be located on the edge of the TLOF shall not exceed a height of 25 cm.</p> <p>(l) Intentionally left blank</p> <p>(m) For any TLOF designed for use by helicopters having a D-value of 16.0 m or less, and any TLOF having dimensions of less than 1 D, objects installed in the obstacle-free sector whose function requires them to be located on the edge of the TLOF, shall not exceed a height of 5 cm.</p> <p>Note.— Lighting that is mounted at a height of less than 25 cm is typically assessed for adequacy of visual cues before and after installation.</p> <p>(n) Objects whose function requires them to be located within the TLOF (such as lighting or nets) shall not exceed a height of 2.5 cm. Such objects shall only be present if they do not represent a hazard to helicopters.</p> <p><i>Note.— Examples of potential hazards include nets or raised fittings on the deck that might induce dynamic rollover for helicopters equipped with skids.</i></p> <p>(o) Safety devices such as safety nets or safety shelves shall be located around the edge of a helideck but shall not exceed the height of the TLOF.</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>(p) The surface of the TLOF shall be skid-resistant to both helicopters and persons and be sloped to prevent pooling of water.</p> <p><i>Note.— Guidance on rendering the surface of the TLOF skidresistant is contained in the Heliport Manual (Doc 9261).</i></p>			
12.2.3.3	<p>SHIPBOARD HELIPOINTS</p> <p>(a) The specifications in paragraphs 12.2.3.3(p) and 12.2.3.3(q) shall be applicable to shipboard heliports completed on or after 1 January 2012 and 1 January 2015, respectively.</p> <p>(b) When helicopter operating areas are provided in the bow or stern of a ship or are purpose-built above the ship's structure, they shall be regarded as purpose-built shipboard heliports.</p> <p>FATOs AND TLOFs</p> <p><i>Note. — Except for the arrangement described 12.2.3.4(h)(2), for shipboard heliports it is presumed that the FATO and the TLOF will be coincidental. Guidance on the effects of airflow direction and turbulence, prevailing wind velocity and high temperature from gas turbine exhausts or flare-radiated heat on the location of the FATO is given in the Heliport Manual (Doc 9261).</i></p> <p>(c) A shipboard heliport shall be provided with one FATO and one coincidental or collocated TLOF.</p> <p>(d) A FATO may be any shape but shall be of sufficient size to contain an area within which can be accommodated a circle of diameter of not less than 1 D of the largest helicopter the heliport is intended to serve.</p> <p>(e) The TLOF of a shipboard heliport shall be dynamic load-bearing.</p> <p>(f) The TLOF of a shipboard heliport shall provide ground effect.</p>			



STATEMENT OF COMPLIANCE

- (g) For purpose-built shipboard heliports provided in a location other than the bow or stern, the TLOF shall be of sufficient size to contain a circle with a diameter not less than 1 D of the largest helicopter the heliport is intended to serve.
- (h) For purpose-built shipboard heliports provided in the bow or stern of a ship, the TLOF shall be of sufficient size to:
 - (1) contain a circle with a diameter not less than 1 D of the largest helicopter the heliport is intended to serve; or
 - (2) for operations with limited touchdown directions, contain an area within which can be accommodated two opposing arcs of a circle with a diameter of not less than 1 D in the helicopter's longitudinal direction. The minimum width of the heliport shall be not less than 0.83 D. (See Figure 3-10.)

Note 1.— The ship will need to be maneuvered to ensure that the relative wind is appropriate to the direction of the helicopter touchdown heading.

Note 2.— The touchdown heading of the helicopter is limited to the angular distance subtended by the 1 D arc headings, minus the angular distance which corresponds to 15 degrees at each end of the arc.

- (i) For non-purpose-built shipboard heliports, the TLOF shall be of sufficient size to contain a circle with a diameter not less than 1 D of the largest helicopter the heliport is intended to serve.
- (j) A shipboard heliport shall be arranged to ensure that a sufficient and unobstructed air-gap is provided which encompasses the full dimensions of the FATO.

Note.— Specific guidance on the characteristics of an air-gap is given in the Heliport Manual (Doc 9261). As a general rule, except for shallow superstructures of three stories or less, a sufficient air-gap will be at least 3 m.



STATEMENT OF COMPLIANCE

	<p>(k) The FATO shall be located so as to avoid, as far as is practicable, the influence of environmental effects, including turbulence, over the FATO, which could have an adverse impact on helicopter operations.</p> <p>(l) No fixed object shall be permitted around the edge of the TLOF except for frangible objects, which, because of their function, must be located thereon.</p> <p>(m) For any TLOF 1D or greater and any TLOF designed for use by helicopters having a D-value of greater than 16.0 m, objects installed in the obstacle-free sector whose function requires them to be located on the edge of the TLOF shall not exceed a height of 25 cm.</p> <p>(n) Intentionally left blank</p> <p>(o) For any TLOF designed for use by helicopters having a D-value of 16.0m or less, and any TLOF having dimensions of less than 1D, objects in the obstacle-free sector, whose function requires them to be located on the edge of the TLOF, shall not exceed a height of 5 cm.</p> <p><i>Note.- Lighting that is mounted at a height of less than 25 cm is typically assessed for adequacy of visual cues before and after installation.</i></p> <p>(p) Objects whose function requires them to be located within the TLOF (such as lighting or nets) shall not exceed a height of 2.5 cm. Such objects shall only be present if they do not represent a hazard to helicopters.</p> <p>(q) Safety devices such as safety nets or safety shelves shall be located around the edge of a shipboard heliport, except where structural protection exists, but shall not exceed the height of the TLOF.</p> <p>(r) The surface of the TLOF shall be skid-resistant to both helicopters and persons.</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

<p>12.2.4</p>	<p>OBSTACLE ENVIRONMENT</p> <p><i>Note.— The objectives of the specifications in this chapter are to describe the airspace around heliports so as to permit intended helicopter operations to be conducted safely and to prevent, where appropriate State controls exist, heliports from becoming unusable by the growth of obstacles around them. This is achieved by establishing a series of obstacle limitation surfaces that define the limits to which objects may project into the airspace.</i></p>			
<p>12.2.4.1</p>	<p>OBSTACLE LIMITATION SURFACES AND SECTORS APPROACH SURFACE</p> <p>(a) Description. An inclined plane or a combination of planes or, when a turn is involved, a complex surface sloping upwards from the end of the safety area and centered on a line passing through the center of the FATO.</p> <p><i>Note.— See Table 4-1 for dimensions and slopes of surfaces. See Figures 4-1, 4-2, 4-3 and 4-4 for depiction of surfaces.</i></p> <p>(b) CHARACTERISTICS. The limits of an approach surface shall comprise:</p> <p>(1) an inner edge horizontal and equal in length to the minimum specified width/diameter of the FATO plus the safety area, perpendicular to the centre line of the approach surface and located at the outer edge of the safety area;</p> <p>(2) two side edges originating at the ends of the inner edge diverging uniformly at a specified rate from the vertical plane containing the centre line of the FATO; and</p> <p>(3) An outer edge horizontal and perpendicular to the centre line of the approach surface and at a specified height of 152 m (500 ft) above the elevation of the FATO.</p> <p>(c) The elevation of the inner edge shall be the elevation of the FATO at the point on the inner edge that is intersected by the</p>			



STATEMENT OF COMPLIANCE

center line of the approach surface. For heliports intended to be used by helicopters operated in performance class 1 and when approved by an appropriate authority, the origin of the inclined plane may be raised directly above the FATO.

- (d) The slope(s) of the approach surface shall be measured in the vertical plane containing the center line of the surface.
- (e) In the case of an approach surface involving a turn, the surface shall be a complex surface containing the horizontal normal to its center line and the slope of the center line shall be the same as that for a straight approach surface.

Note.— See Figure 4-5.

- (f) In the case of an approach surface involving a turn, the surface shall not contain more than one curved portion.
- (g) Where a curved portion of an approach surface is provided, the sum of the radius of arc defining the center line of the approach surface and the length of the straight portion originating at the inner edge shall not be less than 575 m.
- (h) Any variation in the direction of the center line of an approach surface shall be designed so as not to necessitate a turn radius less than 270 m.

Note.— For heliports intended to be used by helicopters operated in performance class 2 or 3, it is good practice for the approach paths to be selected so as to permit safe forced landings or one-engine inoperative landings such that, as a minimum requirement, injury to persons on the ground or water or damage to property are minimized. The most critical helicopter type for which the heliport is intended and the ambient conditions may be factors in determining the suitability of such areas.



STATEMENT OF COMPLIANCE

	<p>TRANSITIONAL SURFACE</p> <p><i>Note.— For a FATO at a heliport without a PinS approach incorporating a visual segment surface (VSS) there is no requirement to provide transitional surfaces.</i></p> <p>(i) DESCRIPTION. A complex surface along the side of the safety area and part of the side of the approach/take-off climb surface, that slopes upwards and outwards to a predetermined height of 45 m (150 ft).</p> <p><i>Note.— See Figure 4-3. See Table 4-1 for dimensions and slopes of surfaces.</i></p> <p>(j) CHARACTERISTICS. The limits of a transitional surface shall comprise:</p> <p>(1) a lower edge beginning at a point on the side of the approach/take-off climb surface at a specified height above the lower edge extending down the side of the approach/take-off climb surface to the inner edge of the approach/take-off climb surface and from there along the length of the side of the safety area parallel to the centre line of the FATO; and</p> <p>(2) an upper edge located at a specified height above the lower edge as set out in Table 4 -1</p> <p>(k) The elevation of a point on the lower edge shall be:</p> <p>(1) along the side of the approach/take-off climb surface — equal to the elevation of the approach/take-off climb surface at that point; and</p> <p>(2) along the safety area — equal to the elevation of the inner edge of the approach/take-off climb surface.</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p><i>Note 1.— If the origin of the inclined plane of the approach/take-off climb surface is raised as approved by an appropriate authority, the elevation of the origin of the transitional surface will be raised accordingly.</i></p> <p><i>Note 2.— As a result of b), the transitional surface along the safety area will be curved if the profile of the FATO is curved, or a plane if the profile is a straight line.</i></p> <p>(l) The slope of the transitional surface shall be measured in a vertical plane at right angles to the centre line of the FATO.</p> <p>TAKE-OFF CLIMB SURFACE</p> <p>(m) DESCRIPTION. An inclined plane, a combination of planes or, when a turn is involved, a complex surface sloping upwards from the end of the safety area and centered on a line passing through the center of the FATO.</p> <p><i>Note. — See Table 4-1 for dimensions and slopes of surfaces. See Figures 4-1, 4-2, 4-3 and 4-4 for depiction of surfaces.</i></p> <p>(n) CHARACTERISTICS. The limits of a take-off climb surface shall comprise:</p> <ol style="list-style-type: none"> (1) an inner edge horizontal and equal in length to the minimum specified width/diameter of the FATO plus the safety area, perpendicular to the center line of the take-off climb surface and located at the outer edge of the safety area; (2) two side edges originating at the ends of the inner edge and diverging uniformly at a specified rate from the vertical plane containing the center line of the FATO; and (3) an outer edge horizontal and perpendicular to the center line of the take-off climb surface and at a specified height of 152 m (500 ft) above the elevation of the FATO. 			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>(o) The elevation of the inner edge shall be the elevation of the FATO at the point on the inner edge that is intersected by the center line of the take-off climb surface. For heliports intended to be used by helicopters operated in performance class 1 and when approved by an appropriate authority, the origin of the inclined plane may be raised directly above the FATO.</p> <p>(p) Where a clearway is provided, the elevation of the inner edge of the take-off climb surface shall be located at the outer edge of the clearway at the highest point on the ground based on the center line of the clearway.</p> <p>(q) In the case of a straight take-off climb surface, the slope shall be measured in the vertical plane containing the center line of the surface.</p> <p>(r) In the case of a take-off climb surface involving a turn, the surface shall be a complex surface containing the horizontal normals to its center line and the slope of the center line shall be the same as that for a straight take-off climb surface.</p> <p><i>Note.— See Figure 4-5.</i></p> <p>(s) In the case of a take-off climb surface involving a turn, the surface shall not contain more than one curved portion.</p> <p>(t) Where a curved portion of a take-off climb surface, is provided, the sum of the radius of arc defining the center line of the take-off climb surface and the length of the straight portion originating at the inner edge shall not be less than 575 m.</p> <p>(u) Any variation in the direction of the center line of a take-off climb surface shall be designed so as not to necessitate a turn of radius less than 270 m.</p> <p><i>Note 1.— Helicopter take-off performance is reduced in a curve and as such a straight portion along the take-off climb surface prior to the start of the curve allows for acceleration.</i></p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

Note 2.— For heliports intended to be used by helicopters operated in performance class 2 or 3, it is good practice for the departure paths to be selected so as to permit safe forced landings or one engine-inoperative landings such that, as a minimum requirement, injury to persons on the ground or water or damage to property are minimized. The most critical helicopter type for which the heliport is intended and the ambient conditions may be factors in determining the suitability of such areas.

OBSTACLE-FREE SECTOR/SURFACE — HELIDECKS

- (v) **DESCRIPTION.** A complex surface originating at and extending from a reference point on the edge of the FATO of a helideck. In the case of a TLOF of less than 1 D, the reference point shall be located not less than 0.5 D from the center of the TLOF.
- (w) **CHARACTERISTICS.** An obstacle-free sector/surface shall subtend an arc of specified angle.
- (x) A helideck obstacle-free sector shall comprise of two components, one above and one below helideck level:

Note.— See Figure 4-7.

- (1) **Above helideck level.** The surface shall be a horizontal plane level with the elevation of the helideck surface that subtends an arc of at least 210 degrees with the apex located on the periphery of the D circle extending outwards to a distance that will allow for an unobstructed departure path appropriate to the helicopter the helideck is intended to serve.
- (2) **Below helideck level.** Within the (minimum) 210-degree arc, the surface shall additionally extend downward from the edge of the FATO below the elevation of the helideck to water level for an arc of not less than 180 degrees that passes through the center of the FATO and outwards to a distance that will allow for safe clearance from the obstacles below the helideck in the event of an engine failure for the type of helicopter the helideck is intended to serve.



STATEMENT OF COMPLIANCE

	<p><i>Note.— For both the above obstacle-free sectors for helicopters operated in performance class 1 or 2, the horizontal extent of these distances from the helideck will be compatible with the one-engineinoperative capability of the helicopter type to be used.</i></p> <p>LIMITED OBSTACLE SECTOR/SURFACE — HELIDECKS</p> <p><i>Note.— Where obstacles are necessarily located on the structure, a helideck may have a limited obstacle sector (LOS).</i></p> <p>(y) DESCRIPTION. A complex surface originating at the reference point for the obstacle-free sector and extending over the arc not covered by the obstacle-free sector within which the height of obstacles above the level of the TLOF will be prescribed.</p> <p>(z) CHARACTERISTICS. A limited obstacle sector shall not subtend an arc greater than 150 degrees. Its dimensions and location shall be as indicated in Figure 4-8 for a 1 D FATO with coincidental TLOF and Figure 4-9 for a 0.83 D TLOF.</p>			
12.2.4.2	<p>OBSTACLE LIMITATION REQUIREMENTS</p> <p><i>Note 1.— The requirements for obstacle limitation surfaces are specified on the basis of the intended use of a FATO, i.e. approach manoeuvre to hover or landing, or take-off manoeuvre and type of approach, and are intended to be applied when such use is made of the FATO. In cases where operations are conducted to or from both directions of a FATO, then the function of certain surfaces may be nullified because of more stringent requirements of another lower surface.</i></p> <p><i>Note 2.— Guidance on obstacle protection surfaces, for when a visual approach slope indicator (VASI) is installed, is given in the onshore section of the Heliport Manual (Doc 9261).</i></p> <p>SURFACE-LEVEL HELIPOINTS</p> <p>(a) The following obstacle limitation surfaces shall be established for a FATO at heliports with a PinS approach procedure utilizing a visual segment surface:</p>			



STATEMENT OF COMPLIANCE

	<p>(1) take-off climb surface; (2) approach surface; and (3) transitional surfaces</p> <p><i>Note 1.— See Figure 4-3.</i></p> <p><i>Note 2.— The Procedures for Air Navigation Services — Aircraft Operations, (PANS-OPS, Doc 8168), Volume II, Part IV details procedure design criteria.</i></p> <p>(b) The following obstacle limitation surfaces shall be established for a FATO at heliports, other than specified in 12.2.4.2(a) including heliports with a PinS approach procedure where a visual segment surface is not provided:</p> <p>(1) take-off climb surface; and (2) approach surface.</p> <p>(c) The slopes of the obstacle limitation surfaces shall not be greater than, and their other dimensions not less than, those specified in Table 4-1 and shall be located as shown in Figures 4-1, 4-2 and 4-6.</p> <p>(d) For heliports that have an approach/take-off climb surface with a 4.5 per cent slope design, objects shall be permitted to penetrate the obstacle limitation surface if the results of an aeronautical study approved by an appropriate authority have reviewed the associated risks and mitigation measures.</p> <p><i>Note 1.— The identified objects may limit the heliport operation.</i></p> <p><i>Note 2.— Annex 6, Part 3, provides procedures that may be useful in determining the extent of obstacle penetration.</i></p> <p>(e) New objects or extensions of existing objects shall not be permitted above any of the surfaces in 12.2.4.2(a) and 12.2.4.2(b) except when shielded by an existing immovable object or after an aeronautical study approved by an appropriate</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>authority determines that the object will not adversely affect the safety or significantly affect the regularity of operations of helicopters.</p> <p><i>Note.— Circumstances in which the shielding principle may reasonably be applied are described in the Airport Services Manual (Doc 9137), Part 6.</i></p> <p>(f) Intentionally left blank</p> <p>(g) A surface-level heliport shall have at least one approach and take-off climb surface. An aeronautical study shall be undertaken by an appropriate authority when only a single approach and take-off climb surface is provided considering as a minimum, the following factors:</p> <ol style="list-style-type: none"> (1) the area/terrain over which the flight is being conducted; (2) the obstacle environment surrounding the heliport and the availability of at least one protected side slope; (3) the performance and operating limitations of helicopters intending to use the heliport; and (4) the local meteorological conditions including the prevailing winds. <p>(h) Intentionally left blank</p> <p>ELEVATED HELIPORTS</p> <p>(a) The obstacle limitation surfaces for elevated heliports shall conform to the requirements for surface-level heliports specified in 12.2.4.2(a) to 12.2.4.2(f)</p> <p>(b) An elevated heliport shall have at least one approach and takeoff climb surface. An aeronautical study shall be undertaken by an appropriate authority when only a single approach and takeoff climb surface is provided considering as a minimum, the following factors:</p> <ol style="list-style-type: none"> (1) the area/terrain over which the flight is being conducted 			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>(2) the obstacle environment surrounding the heliport and the availability of at least one protected side slope;</p> <p>(3) the performance and operating limitations of helicopters intending to use the heliport; and</p> <p>(4) the local meteorological conditions including the prevailing winds.</p> <p>(k) Intentionally left blank</p> <p>HELIDECKS</p> <p>(l) A helideck shall have an obstacle-free sector.</p> <p><i>Note.— A helideck may have a LOS (see 12.2.4.1(z)).</i></p> <p>(m) There shall be no fixed obstacles within the obstacle-free sector above the obstacle-free surface.</p> <p>(n) In the immediate vicinity of the helideck, obstacle protection for helicopters shall be provided below the helideck level. This protection shall extend over an arc of at least 180 degrees with the origin at the centre of the FATO, with a descending gradient having a ratio of one unit horizontally to five units vertically from the edges of the FATO within the 180-degree sector. This descending gradient may be reduced to a ratio of one unit horizontally to three units vertically within the 180-degree sector for multi-engine helicopters operated in performance class 1 or 2. (See Figure 4-7.)</p> <p><i>Note.— Where there is a requirement to position, at sea surface level, one or more offshore support vessel(s) (e.g. a Standby Vessel)</i></p> <p>essential to the operation of a fixed or floating offshore facility, but located within the proximity of the fixed or floating offshore facility, any offshore support vessel(s) would need to be positioned so as not to</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>compromise the safety of helicopter operations during take-off departure and/or approach to landing.</p> <p>(o) For a TLOF of 1 D and larger, within the 150-degree limited obstacle surface/sector out to a distance of 0.12 D measured from the point of origin of the LOS, objects shall not exceed a height of 25 cm above the TLOF. Beyond that arc, out to an overall distance of a further 0.21 D measured from the end of the first sector, the limited obstacle surface rises at a rate of one unit vertically for each two units horizontally originating at a height 0.05 D above the level of the TLOF. (See Figure 4-8.)</p> <p><i>Note.— Where the area enclosed by the TLOF perimeter marking is a shape other than circular, the extent of the LOS segments are represented as lines parallel to the perimeter of the TLOF rather than arcs. Figure 4-8 has been constructed on the assumption that an octagonal helideck arrangement is provided. Further guidance for square (quadrilateral) and circular FATO and TLOF arrangements is given in the Heliport Manual (Doc 9261).</i></p> <p>(p) For a TLOF less than 1 D within the 150-degree limited obstacle surface/sector out to a distance of 0.62 D and commencing from a distance 0.5 D, both measured from the centre of the TLOF, objects shall not exceed a height of 5 cm above the TLOF.</p> <p>Beyond that arc, out to an overall distance of 0.83 D from the centre of the TLOF, the limited obstacle surface rises at a rate of one unit vertically for each two units horizontally originating at a height 0.05 D above the level of the TLOF. (See Figure 4-9.)</p> <p><i>Note.— Where the area enclosed by the TLOF perimeter marking is a shape other than circular, the extent of the LOS segments are represented as lines parallel to the perimeter of the TLOF rather than arcs. Figure 4-9 has been constructed on the assumption that an octagonal helideck arrangement is provided. Further guidance for square (quadrilateral) and circular FATO and TLOF arrangements is given in the Heliport Manual (Doc 9261).</i></p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>SHIPBOARD HELIPOINTS</p> <p>(q) The specifications in 1 2 . 2 . 4(b)20 and 1 2 . 2 . 4(b)22 shall be applicable for shipboard heliports completed on or after 1 January 2012.</p> <p>(r) PURPOSE-BUILT HELIPOINTS LOCATED FORWARD OR AFT When helicopter operating areas are provided in the bow or stern of a ship they shall apply the obstacle criteria for helidecks.</p> <p>(s) AMIDSHIPS LOCATION — PURPOSE-BUILT AND NONPURPOSE- BUILT Forward and aft of a TLOF of 1 D and larger shall be two symmetrically located sectors, each covering an arc of 150 degrees, with their apexes on the periphery of the TLOF. Within the area enclosed by these two sectors, there shall be no objects rising above the level of the TLOF, except those aids essential for the safe operation of a helicopter and then only up to a maximum height of 25 cm.</p> <p>(s) Objects whose function requires them to be located within the TLOF (such as lighting or nets) shall not exceed a height of 2.5 cm. Such objects shall only be present if they do not represent a hazard to helicopters.</p> <p><i>Note.— Examples of potential hazards include nets or raised fittings on the deck that might induce dynamic rollover for helicopters equipped with skids.</i></p> <p>(t) To provide further protection from obstacles fore and aft of the TLOF, rising surfaces with gradients of one unit vertically to five units horizontally shall extend from the entire length of the edges of the two 150-degree sectors. These surfaces shall extend for a horizontal distance equal to at least 1 D of the largest helicopter the TLOF is intended to serve and shall not be penetrated by any obstacle. (See Figure 4-10.)</p> <p>(v) NON-PURPOSE-BUILT HELIPOINTS — SHIP'S SIDE LOCATION No objects shall be located within the TLOF except those aids essential for the safe operation of a helicopter (such as nets or lighting) and then</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>only up to a maximum height of 2.5 cm. Such objects shall only be present if they do not represent a hazard to helicopters.</p> <p>(w) From the fore and aft mid-points of the D circle in two segments outside the circle, limited obstacle areas shall extend to the ship's rail to a fore and aft distance of 1.5 times the fore-to-aft dimension of the TLOF, located symmetrically about the athwart ships bisector of the D circle. Within these areas there shall be no objects rising above a maximum height of 25 cm above the level of the TLOF. (See Figure 4-11.) Such objects shall only be present if they do not represent a hazard to helicopters.</p> <p>(x) A LOS horizontal surface shall be provided, at least 0.25 D beyond the diameter of the D circle, which shall surround the inboard sides of the TLOF to the fore and aft mid-points of the D circle. The LOS shall continue to the ship's rail to a fore and aft distance of 2.0 times the fore-to-aft dimension of the TLOF, located symmetrically about the athwart ships bisector of the D circle. Within this sector there shall be no objects rising above a maximum height of 25 cm above the level of the TLOF.</p> <p><i>Note.— Any objects located within the areas described in 12.2.4.2(w) and 12.2.4.2(x) that exceed the height of the TLOF are notified to the helicopter operator using a ship's helicopter landing area plan. For notification purposes, it may be necessary to consider immovable objects beyond the limit of the surface prescribed in 12.2.4.2(x), particularly if objects are significantly higher than 25 cm and in close proximity to the boundary of the LOS. See the Heliport Manual (Doc 9261) for guidance.</i></p> <p>(y) WINCHING AREAS</p> <p>An area designated for winching on-board ships shall be comprised of a circular clear zone of diameter 5 m and, extending from the perimeter of the clear zone, a concentric manoeuvring zone of diameter 2 D. (See Figure 4-12.)</p> <p>(z) The manoeuvring zone shall be comprised of two areas: (1) the inner manoeuvring zone extending from the perimeter of the</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>clear zone and of a circle of diameter not less than 1.5 D; and (2) the outer manoeuvring zone extending from the perimeter of the inner manoeuvring zone and of a circle of diameter not less than 2 D.S</p> <p>(aa) Within the clear zone of a designated winching area, no objects shall be located above the level of its surface.</p> <p>(ab) Objects located within the inner manoeuvring zone of a designated winching area shall not exceed a height of 3 m.</p> <p>(ac) Objects located within the outer manoeuvring zone of a designated winching area shall not exceed a height of 6 m.</p> <p><i>Note.— See the Heliport Manual (Doc 9261) for guidance</i></p>			
<p>12.2.5</p>	<p>VISUAL AIDS</p> <p><i>Note 1.— The procedures used by some helicopters require that they utilize a FATO having characteristics similar in shape to a runway for fixed wing aircraft. For the purpose of this chapter, a FATO having characteristics similar in shape to a runway is considered as satisfying the concept for a “runway-type FATO”. For such arrangements it is sometimes necessary to provide specific markings to enable a pilot to distinguish a runway-type FATO during an approach. Appropriate markings are contained within sub-sections entitled “Runway-type FATOs”. The requirements applicable to all other types of FATOs are given within sub-sections entitled “All FATOs except runway-type FATOs”.</i></p> <p><i>Note 2.— It has been found that, on surfaces of light colour, the conspicuity of white and yellow markings can be improved by outlining them in black.</i></p> <p><i>Note 3.— Guidance is given in the Heliport Manual (Doc 9261) on marking the maximum allowable mass (5.2.3) and the D-value (5.2.4)</i></p>			



STATEMENT OF COMPLIANCE

	<p><i>on the heliport surface to avoid confusion between markings where metric units are used and markings where imperial units are used.</i></p> <p><i>Note 4.— For a non-purpose-built heliport located on a ship's side the surface colour of the main deck can vary from ship to ship and therefore some discretion may need to be exercised in the colour selection of heliport paint schemes, the objective being to ensure that the markings are conspicuous against the surface of the ship and the operating background.</i></p>			
12.2.5.1	<p>INDICATORS</p> <p>(a) WIND DIRECTION INDICATORS\ (1) APPLICATION A heliport shall be equipped with at least one wind direction indicator. (2) LOCATION A wind direction indicator shall be located so as to indicate the wind conditions over the FATO and TLOF and in such a way as to be free from the effects of airflow disturbances caused by nearby objects or rotor downwash. It shall be visible from a helicopter in flight, in a hover or on the movement area. (3) Intentionally left blank (4) CHARACTERISTICS</p>			
12.2.5.1	<p>INDICATORS</p> <p>(a) WIND DIRECTION INDICATORS</p> <p>(1) APPLICATION A heliport shall be equipped with at least one wind direction indicator.</p> <p>(2) LOCATION A wind direction indicator shall be located so as to indicate the wind conditions over the FATO and TLOF and in such a way as to be free from the effects of airflow disturbances caused by nearby objects or rotor downwash. It shall be visible from a helicopter in flight, in a hover or on the movement area. (3) Intentionally left blank (4) CHARACTERISTICS</p>			



STATEMENT OF COMPLIANCE

	<p>A wind direction indicator shall be constructed so that it gives a clear indication of the direction of the wind and a general indication of the wind speed.</p> <p>(5) A wind direction indicator shall be a truncated cone made of lightweight fabric and shall have the following minimum dimensions:</p> <p>6) The colour of the wind direction indicator shall be so selected as to make it clearly visible and understandable from a height of at least 200 m (650 ft) above the heliport, having regard to background. Where practicable, a single colour, preferably white or orange, shall be used. Where a combination of two colours is required to give adequate conspicuity against changing backgrounds, they shall preferably be orange and white, red and white, or black and white, and shall be arranged in five alternate bands the first and last band being the darker colour.</p> <p>(7) A wind direction indicator at a heliport intended for use at night shall be illuminated.</p>			
12.2.5.2	<p>MARKINGS AND MARKERS <i>Note.— See Nig. CARs Part 12 Volume I, 12.2.5.2(a)4, Note 1, concerning improving conspicuity of markings.</i></p> <p>(a) WINCHING AREA MARKING</p> <p><i>Note.— The objective of winching area markings is to provide to the pilot visual cues to assist a helicopter to be positioned over, and retained within, an area from which a passenger or equipment can be lowered or raised.</i></p> <p>(1) APPLICATION Winching area markings shall be provided at a designated winching area. (See Figure 4-12.)</p> <p>(2) LOCATION Winching area markings shall be located so that their centre(s) coincides with the centre of the clear zone of the winching area. (See Figure 4-12.)</p>			



STATEMENT OF COMPLIANCE

	<p>CHARACTERISTICS</p> <p>(3) Winching area markings shall comprise a winching area clear zone marking and a winching area manoeuvring zone marking.</p> <p>(4) A winching area clear zone marking shall consist of a solid circle of diameter not less than 5 m and of a conspicuous colour.</p> <p>(5) A winching area manoeuvring zone marking shall consist of a broken circle line of 30 cm in width and of a diameter not less than 2 D and be marked in a conspicuous colour. Within it "WINCH ONLY" shall be marked to be easily visible to the pilot.</p> <p>(b) HELIPORT IDENTIFICATION MARKING</p> <p>(1) APPLICATION A heliport identification marking shall be provided at a heliport.</p> <p>LOCATION — ALL FATO_s EXCEPT RUNWAY-TYPE FATO_s</p> <p>(3) A heliport identification marking shall be located at or near the centre of the FATO.</p> <p><i>Note 1.— The objective of heliport identification marking is to provide to the pilot an indication of the presence of a heliport and, by its form, the likely usage; the preferred direction(s) of approach; or the FATO orientation within the helideck obstacle environment.</i></p> <p><i>Note 2.— For other than helidecks, the preferred direction(s) of approach corresponds to the median of the departure/arrival surface(s).</i></p> <p><i>Note 3.— For helidecks, the bar of the "H" points to the centre of the limited obstacle sector (LOS).</i></p> <p><i>Note 4.— If the touchdown/positioning marking (TDPM) is offset, the heliport identification marking is established in the centre of the TDPM.</i></p> <p><i>Note 5.— On a FATO which does not contain a TLOF and which is marked with an aiming point marking (see 12.2.5.2(g)), the heliport identification marking is established in the centre of the aiming point marking as shown in Figures 5-1 and 5-2.</i></p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>(4) On a FATO which contains a TLOF, a heliport identification marking shall be located in the FATO so the position of it coincides with the centre of the TLOF.</p> <p>LOCATION — RUNWAY-TYPE FATOs</p> <p>(4) A heliport identification marking shall be located in the FATO and when used in conjunction with FATO designation markings, shall be displayed at each end of the FATO as shown in Figure 5-3.</p> <p>CHARACTERISTICS</p> <p>(5) A heliport identification marking, except for a heliport at a hospital, shall consist of a letter H, in white. The dimensions of the H marking shall be no less than those shown in Figure 5-4 and where the marking is used for a runway- type FATO; its dimensions shall be increased by a factor of 3 as shown in Figure 5-3.</p> <p>(6) A heliport identification marking for a heliport at a hospital shall consist of a letter H, red in colour, on a white cross made of squares adjacent to each of the sides of a square containing the H as shown in Figures 5-2 and 5-4.</p> <p>(7) A heliport identification marking shall be oriented with the cross arm of the H at right angles to the preferred final approach direction. For a helideck, the cross arm shall be on or parallel to the bisector of the obstacle-free sector. For a non-purpose-built shipboard heliport located on a ship's side, the cross arm shall be parallel with the side of the ship.</p> <p>(8) Intentionally left blank</p> <p>(c) MAXIMUM ALLOWABLE MASS MARKING. <i>Note 1.— The objective of the maximum allowable mass marking is to provide the mass limitation of the heliport such that it is visible to the pilot from the preferred final approach direction.</i></p> <p><i>pounds, it is not appropriate to suffix with the letter "t" which is used only</i></p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

to indicate metric tonnes. Guidance on markings where States use imperial units is given in the Heliport Manual (Doc 9261).

APPLICATION

- (1) A maximum allowable mass marking shall be displayed at an elevated heliport, a helideck and a shipboard heliport.
- (2) A maximum allowable mass shall be displayed at a surface-level heliport.

LOCATION

- (4) A maximum allowable mass marking shall be located within the TLOF or FATO and so arranged as to be readable from the preferred final approach direction.

CHARACTERISTICS

- (4) A maximum allowable mass marking shall consist of a one-, two- or three-digit number.
- (5) The maximum allowable mass shall be expressed in tonnes (1 000 kg) rounded down to the nearest 1 000 kg followed by the letter "t".
- (6) Intentionally left blank
- (7) Intentionally left blank

ALL FATOs EXCEPT RUNWAY-TYPE FATOs

- (8) The numbers and the letter of the marking should have a colour contrasting with the background and should be in the form and proportion shown in Figure 5 -5 for a D-value of more than 30 m. For a D-value between 15 m and 30 m, the height of the numbers and the letter of the marking should be a minimum of 90 cm, and for a D-value of less than 15 m, the height of the numbers and the letter of the marking should be a minimum of 60 cm, each with a proportional reduction in width and thickness.

RUNWAY-TYPE FATOs

- (9) The numbers and the letter of the marking should have a colour contrasting with the background and should be in the form and proportion shown in Figure 5 -5.



STATEMENT OF COMPLIANCE

	<p>(d) D-VALUE MARKING <i>Note.— The objective of D-value marking is to provide to the pilot the “D” of the largest helicopter that can be accommodated on the heliport. This value may differ in size from the FATO and the TLOF provided in compliance with 12.2.3</i></p> <p>APPLICATION — ALL FATOs EXCEPT RUNWAY-TYPE FATOs (1) A D-value marking shall be displayed at a helideck and at a shipboard heliport.</p> <p>APPLICATION — RUNWAY-TYPE FATOs <i>Note.—The D-value is not required to be marked on a heliport with a runway-type FATO.</i></p> <p>(2) A D-value marking shall be displayed at surface-level and elevated heliports.</p> <p>LOCATION (3) A D-value marking shall be located within the TLOF or FATO and so arranged as to be readable from the preferred final approach direction. (4) Where there is more than one approach direction, additional D-value markings should be provided such that at least one D-value marking is readable from the final approach direction. For a non-purpose-built heliport located on a ship’s side, D-value markings should be provided on the perimeter of the D circle at the 2 o’clock, 10 o’clock and 12 o’clock positions when viewed from the side of the ship facing towards the centre line.</p> <p>CHARACTERISTICS (5) The D-value marking shall be white. The D-value marking shall be rounded to the nearest whole metre or foot with 0.5 rounded down. (6) The numbers of the marking should have a colour contrasting with the background and should be in the form and proportion shown in Figure 5-5 for a D-value of more than 30 m. For a D-value between 15 m and 30 m, the height of the numbers of the marking should be a minimum of 90 cm, and for a D-value of less than 15 m, the height of the</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

numbers of the marking should be a minimum of 60 cm, each with a proportional reduction in width and thickness.

(e) FATO PERIMETER MARKING OR MARKERS FOR SURFACE-LEVEL HELIPORTS

Note.— The objective of FATO perimeter marking or markers is to provide to the pilot, where the perimeter of the FATO is not self-evident, an indication of the area that is free of obstacles and in which intended procedures or permitted manoeuvring may take place.

APPLICATION

- (1) FATO perimeter marking or markers shall be provided at a surface-level heliport where the extent of a FATO with a solid surface is not self-evident.

LOCATION

- (2) The FATO perimeter marking or markers shall be located on the edge of the FATO.

CHARACTERISTICS — RUNWAY-TYPE FATOs

- (3) The perimeter of the FATO shall be defined with markings or markers spaced at equal intervals of not more than 50 m with at least three markings or markers on each side including a marking or marker at each corner.
- (4) A FATO perimeter marking shall be a rectangular stripe with a length of 9 m or one-fifth of the side of the FATO which it defines and a width of 1 m.
- (5) FATO perimeter markings shall be white.
- (6) A FATO perimeter marker shall have dimensional characteristics as shown in Figure 5 -6.
- (7) FATO perimeter markers shall be of colour(s) that contrast effectively against the operating background.
- (8) FATO perimeter markers shall be a single colour, orange or red, or two contrasting colours, orange and white or, alternatively, red and white shall be used except where such colours would merge with the background.



STATEMENT OF COMPLIANCE

	<p>CHARACTERISTICS — ALL FATOS EXCEPT RUNWAY-TYPE FATOS</p> <p>(9) For an unpaved FATO the perimeter shall be defined with flush in-ground markers. The FATO perimeter markers shall be 30 cm in width, 1.5 m in length, and with end-to-end spacing of not less than 1.5 m and not more than 2 m. The corners of a square or rectangular FATO shall be defined.</p> <p>(10) For a paved FATO the perimeter shall be defined with a dashed line. The FATO perimeter marking segments shall be 30 cm in width, 1.5 m in length, and with end-to-end spacing of not less than 1.5 m and not more than 2 m. The corners of the square or rectangular FATO shall be defined.</p> <p>(f) FATO DESIGNATION MARKINGS FOR RUNWAY-TYPE FATOS</p> <p><i>Note.— The objective of final FATO designation markings for runway-type FATOs is to provide to the pilot an indication of the magnetic heading of the runway.</i></p> <p>APPLICATION</p> <p>(1) A FATO designation marking shall be provided at a heliport where it is necessary to designate the FATO to the pilot.</p> <p>LOCATION</p> <p>(3) A FATO designation marking shall be located at the beginning of the final approach and take-off area FATO as shown in Figure 5-3</p> <p>CHARACTERISTICS</p> <p>(3) A FATO designation marking shall consist of a two-digit number. The two digit number shall be the whole number nearest the one-tenth of the magnetic North when viewed from the direction of approach. When the above rule would give a single digit number, it shall be preceded by a zero. The marking as shown in Figure 5-2, shall be supplemented by the heliport identification marking.</p> <p>(f) AIMING POINT MARKING</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p><i>Note.— The objective of the aiming point marking is to provide a visual cue indicating to the pilot the preferred approach/departure direction; the point to which the helicopter approaches to the hover before positioning to a stand where a touchdown can be made; and that the surface of the FATO is not intended for touchdown.</i></p> <p>APPLICATION</p> <p>(1) An aiming point marking shall be provided at a heliport where it is necessary for a pilot to make an approach to a particular point above a FATO before proceeding to a TLOF.</p> <p>LOCATION — RUNWAY-TYPE FATOs</p> <p>(2) The aiming point marking shall be located within the FATO.</p> <p>LOCATION — ALL FATOs EXCEPT RUNWAY-TYPE FATOs</p> <p>(2) The aiming point marking shall be located at the centre of the FATO as shown in Figure 5-1.</p> <p>CHARACTERISTICS</p> <p>(4) The aiming point marking shall be an equilateral triangle with the bisector of one of the angles aligned with the preferred approach direction. The marking shall consist of continuous lines, providing a contrast with the background colour and the dimensions of the marking shall conform to those shown in Figure 5-7.</p> <p>h) TOUCHDOWN AND LIFT-OFF (TLOF) AREA PERIMETER MARKING</p> <p><i>Note.— The objective of TLOF perimeter marking is to provide to the pilot an indication of an area that is free of obstacles; has dynamic load bearing; and in which, when positioned in accordance with the TDPM, undercarriage containment is assured.</i></p> <p>APPLICATION</p> <p>(1) A TLOF perimeter marking shall be displayed on a TLOF located in a FATO at a surface-level heliport if the perimeter of the TLOF is not self-evident.</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>(2) A TLOF perimeter marking shall be displayed on an elevated heliport, a helideck and a shipboard heliport.</p> <p>LOCATION</p> <p>(3) A TLOF perimeter marking shall be located along the edge of the TLOF. CHARACTERISTICS</p> <p>(4) A TLOF perimeter marking shall consist of a continuous white line with a width of at least 30 cm.</p> <p>(i) TOUCHDOWN/POSITIONING MARKING</p> <p><i>Note.— The objective of touchdown/positioning marking (TDPM) is to provide visual cues which permit a helicopter to be placed in a specific position such that, when the pilot's seat is above the marking, the undercarriage is within the load - bearing area and all parts of the helicopter will be clear of any obstacles by a safe margin.</i></p> <p>APPLICATION</p> <p>(1) A TDPM shall be provided for a helicopter to touch down or be accurately placed in a specific position.</p> <p>(2) The TDPM shall be:</p> <p>(i) when there is no limitation on the direction of touchdown/positioning, a touchdown/positioning circle (TDPC) marking; and</p> <p>(ii) when there is a limitation on the direction of touchdown/positioning:</p> <p>(A) for unidirectional applications, a shoulder line with an associated centreline; or</p> <p>(B) for multidirectional applications, a TDPC marking with prohibited landing sector(s) marked. LOCATION</p> <p>(3) The inner edge/inner circumference of the TDPM shall be at a distance of 0.25 D from the centre of the area in which the helicopter is to be positioned.</p> <p>(4) On a helideck, the centre of the TDPC marking shall be located at the centre of the FATO, except that the marking may be offset away from the origin of the obstacle-free sector by no more than 0.1 D where</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>an aeronautical study indicates such offsetting is necessary and would not impair safety.</p> <p>(5) Prohibited landing sector markings, when provided, shall be located on the TDPM, within the relevant headings, and extend to the inner edge of the TLOF perimeter marking.</p> <p>CHARACTERISTICS</p> <p>(5) The inner diameter of the TDPC shall be 0.5 D of the largest helicopter the area is intended to serve.</p> <p>(7) A TDPM shall have a line width of at least 0.5 m. For a helideck and a purpose-built shipboard heliport, the line width shall be at least 1 m.</p> <p>(8) The length of a shoulder line shall be 0.5 D of the largest helicopter the area is intended to serve.</p> <p>(8) The prohibited landing sector marking, when provided, shall be indicated by white and red hatched markings as shown in Figure 5-8</p> <p>(9) The TDPM shall take precedence when used in conjunction with other markings on the TLOF except for the prohibited landing sector marking.</p> <p><i>Note.— The prohibited landing sector marking, when provided, is not intended to move the helicopter away from objects around the FATO, but to ensure that the tail is not placed in an orientation that might constitute a hazard. This is achieved by having the helicopter nose clear of the hatched markings during the touchdown.</i></p> <p>(j) HELIPORT NAME MARKING</p> <p><i>Note.— The objective of heliport name marking is to provide to the pilot a means of identifying a heliport which can be seen, and read, from all directions of approach.</i></p> <p>APPLICATION</p> <p>(1) A heliport name marking shall be provided at a heliport and helideck where there is insufficient alternative means of visual identification.</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>LOCATION (2) Where a limited obstacle sector (LOS) exists on a helideck the marking shall be located on the obstacle side of the heliport identification marking. For a non-purpose-built heliport located on a ship's side the marking shall be located on the inboard side of the heliport identification marking in the area between the TLOF perimeter marking and the boundary of the LOS.</p> <p>CHARACTERISTICS</p> <p>(3) A heliport name marking shall consist of the name or the alphanumeric designator of the heliport as used in the radio (R/T) communications. (4) A heliport name marking intended for use at night or during conditions of poor visibility shall be illuminated, either internally or externally.</p> <p>RUNWAY-TYPE FATOS (5) The characters of the marking shall be not less than 3 m in height.</p> <p>ALL FATOS EXCEPT RUNWAY-TYPE FATOS. (6) The characters of the marking shall be not less than 1.5 m in height at surface-level heliports and not less than 1.2 m on elevated heliports, helidecks and shipboard heliports. The colour of the marking shall contrast with the background and preferably be white.</p> <p>(k) HELIDECK OBSTACLE-FREE SECTOR (CHEVRON) MARKING <i>Note.— The objective of helideck obstacle-free sector (chevron) marking is to indicate the direction and limits of a sector that is free of obstacles above the level of the helideck for the preferred approach and departure directions.</i></p> <p>APPLICATION (1) A helideck with adjacent obstacles that penetrate above the level of the helideck shall have an obstacle-free sector marking.</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>LOCATION</p> <p>(2) A helideck obstacle-free sector marking shall be located, where practicable, at a distance from the centre of the TLOF equal to the radius of the largest circle that can be drawn in the TLOF or 0.5 D, whichever is greater.</p> <p><i>Note.— Where the point of origin is outside the TLOF, and it is not practicable to physically paint the chevron, the chevron is relocated to the TLOF perimeter on the bisector of the obstacle-free sector. In this case, the distance and direction of displacement, along with the attention getting “WARNING DISPLACED CHEVRON”, is marked in a box beneath the chevron in black characters not less than 10 cm high. (An example figure is given in the Heliport Manual (Doc 9261).)</i></p> <p>CHARACTERISTICS</p> <p>(3) The helideck obstacle-free sector marking shall indicate the location of the obstacle-free sector and the directions of the limits of the sector.</p> <p><i>Note.— Example figures are given in the Heliport Manual (Doc 9261).</i></p> <p>(4) The height of the chevron shall not be less than 30 cm. (5) The chevron shall be marked in a conspicuous colour. (6) The colour of the chevron shall be black.</p> <p>(I) HELIDECK AND SHIPBOARD HELIPORT SURFACE MARKING</p> <p><i>Note.— The objective of helideck and shipboard heliport surface marking is to provide to the pilot, by colour and conspicuity, the location of the TLOF on a helideck or shipboard heliport.</i></p> <p>APPLICATION</p> <p>(1) A surface marking shall be provided to assist the pilot to identify the location of the helideck or shipboard heliport during an approach by day.</p> <p>LOCATION</p> <p>(2) A surface marking shall be applied to the dynamic load-bearing area</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>bounded by the TLOF perimeter marking.</p> <p>CHARACTERISTICS</p> <p>(3) The helideck or shipboard heliport surface bounded by the TLOF perimeter marking shall be of dark green using a high friction coating.</p> <p><i>Note.— Where the application of a surface coating may have a degrading effect on friction qualities, the surface might not be painted. In such cases, the best operating practice to enhance the conspicuity of markings is to outline deck markings with a contrasting colour.</i></p> <p>(m) HELICOPTER TAXIWAY MARKINGS AND MARKERS</p> <p><i>Note 1.— The objective of helicopter taxiway markings and markers is, without being a hazard to the helicopter, to provide to the pilot by day and, if necessary, by night, visual cues to guide movement along the taxiway</i></p> <p><i>.Note 2.— The specifications for runway-holding position markings in Fig. CARs 12.2.5.2(j) volume 1 are equally applicable to taxiways intended for ground taxiing of helicopters.</i></p> <p><i>Note 3.— Ground taxi-routes and air taxi-routes over a taxiway are not required to be marked.</i></p> <p><i>Note 4.— Unless otherwise indicated, it may be assumed that a helicopter taxiway is suitable for both ground taxiing and air taxiing of helicopters.</i></p> <p><i>Note 5.— Signage may be required on an aerodrome where it is necessary to indicate that a helicopter taxiway is suitable only for the use of helicopters.</i></p> <p>APPLICATION</p> <p>(1) The centre line of a helicopter taxiway shall be identified with a marking.</p> <p>(2) The edges of a helicopter taxiway, if not self-evident, shall be identified with markers or markings.</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>LOCATION</p> <p>(3) Helicopter taxiway markings shall be along the centre line and, if required, along the edges of a helicopter taxiway.</p> <p>(4) Helicopter taxiway edge markers shall be located at a distance of 1 m to 3 m beyond the edge of the helicopter taxiway.</p> <p>(5) Helicopter taxiway edge markers shall be spaced at intervals of not more than 15 m on each side of straight sections and 7.5 m on each side of curved sections with a minimum of four equally spaced markers per section.</p> <p>CHARACTERISTICS</p> <p>(6) On a paved taxiway, a helicopter taxiway centre line marking shall be a continuous yellow line 15 cm in width.</p> <p>(7) On an unpaved taxiway that will not accommodate painted markings, a helicopter taxiway centre line shall be marked with flush in-ground 15-cm wide and approximately 1.5 m in length yellow markers, spaced at intervals of not more than 30 m on straight sections and not more than 15 m on curves, with a minimum of four equally spaced markers per section.</p> <p>(8) Helicopter taxiway edge markings shall be a continuous double yellow line, each 15 cm in width, and spaced 15 cm apart (nearest edge to nearest edge).</p> <p>(9) A helicopter taxiway edge marker shall be frangible to the wheeled undercarriage of a helicopter.</p> <p>(10) A helicopter taxiway edge marker shall not exceed a plane originating at a height of 25 cm above the plane of the helicopter taxiway, at a distance of 0.5 m from the edge of the helicopter taxiway and sloping upwards and outwards at a gradient of 5 per cent to a distance of 3 m beyond the edge of the helicopter taxiway.</p> <p>(11) A helicopter taxiway edge marker shall be blue.</p> <p><i>Note 1.— Guidance on suitable edge markers is given in the Heliport Manual (Doc 9261).</i></p> <p><i>Note 2.— If blue markers are used on an aerodrome, signage may be required to indicate that the helicopter taxiway is suitable only for helicopters.</i></p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>(12) If the helicopter taxiway is to be used at night, the edge markers shall be internally illuminated or retro- reflective.</p> <p>(n) HELICOPTER AIR TAXI-ROUTE MARKINGS AND MARKERS <i>Note.— The objective of helicopter air taxi-route markings and markers is to provide to the pilot by day and, if necessary, by night, visual cues to guide movement along the air taxi-route.</i></p> <p>APPLICATION (1) The centre line of a helicopter air taxi-route shall be identified with markers or markings.</p> <p>LOCATION (3) A helicopter air taxi-route centre line marking or flush in-ground centre line marker shall be located along the centre line of the helicopter air taxi-route.</p> <p>CHARACTERISTICS (3) A helicopter air taxi-route centre line, when on a paved surface, shall be marked with a continuous yellow line 15 cm in width. (4) A helicopter air taxi-route centre line, when on an unpaved surface that will not accommodate painted markings, shall be marked with flush in-ground 15-cm-wide and approximately 1.5 m in length yellow markers, spaced at intervals of not more than 30 m on straight sections and not more than 15 m on curves, with a minimum of four equally spaced markers per section. (5) If the helicopter air taxi-route is to be used at night, markers shall be either internally illuminated or retro- reflective.</p> <p>(o) HELICOPTER STAND MARKINGS <i>Note.— The objective of helicopter stand markings is to provide to the pilot a visual indication of: an area that is free of obstacles and in which permitted manoeuvring, and all necessary ground functions, may take place; identification, mass and D-value limitations, when required; and guidance for manoeuvring and positioning of the helicopter within the stand.</i></p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>APPLICATION (1) A helicopter stand perimeter marking shall be provided. (2) A helicopter stand shall be provided with the appropriate TDPM. See Figure 5-8. (3) Alignment lines and lead-in/lead-out lines shall be provided on a helicopter stand.</p> <p><i>Note 1.— See 12.2.3, Figures 3.5 to 3.9.</i> <i>Note 2.— Helicopter stand identification markings may be provided where there is a need to identify individual stands.</i> <i>Note 3.— Additional markings relating to stand size may be provided. See the Heliport Manual (Doc 9261).</i></p> <p>LOCATION (4) The TDPM, alignment lines and lead-in/lead-out lines shall be located such that every part of the helicopter can be contained within the helicopter stand during positioning and permitted manoeuvring. (5) Alignment lines and lead-in/lead-out lines shall be located as shown in Figure 5-9.</p> <p>CHARACTERISTICS (6) A helicopter stand perimeter marking shall consist of a continuous yellow line and have a line width of 15 cm. (7) The TDPM shall have the characteristics described in paragraph 12.2.5.2(i) above. (8) Alignment lines and lead-in/lead-out lines shall be continuous yellow lines and have a width of 15 cm. (9) Curved portions of alignment lines and lead-in/lead-out lines shall have radii appropriate to the most demanding helicopter type the helicopter stand is intended to serve. (10) Stand identification markings shall be marked in a contrasting colour so as to be easily readable .</p> <p>p) FLIGHT PATH ALIGNMENT GUIDANCE MARKING</p> <p><i>Note.— The objective of flight path alignment guidance marking is to provide the pilot with a visual indication of the available approach and/or departure path direction(s)</i></p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>APPLICATION (1) Flight path alignment guidance marking(s) shall be provided at a heliport where it is desirable and practicable to indicate available approach and/or departure path direction(s).</p> <p><i>Note.— The flight path alignment guidance marking can be combined with a flight path alignment guidance lighting system described in 12.2.5.3(d)</i></p> <p>LOCATION (2) The flight path alignment guidance marking shall be located in a straight line along the direction of approach and/or departure path on one or more of the TLOF, FATO, safety area or any suitable surface in the immediate vicinity of the FATO or safety area.</p> <p>CHARACTERISTICS (3) A flight path alignment guidance marking shall consist of one or more arrows marked on the TLOF, FATO and/or safety area surface as shown in Figure 5-10. The stroke of the arrow(s) shall be 50 cm in width and at least 3 m in length. When combined with a flight path alignment guidance lighting system it shall take the form shown in Figure 5 -10 which includes the scheme for marking “heads of the arrows” which are constant regardless of stroke length.</p> <p><i>Note.— In the case of a flight path limited to a single approach direction or single departure direction, the arrow marking may be unidirectional. In the case of a heliport with only a single approach/departure path available, one bidirectional arrow is marked.</i></p> <p>(4) The markings shall be in a colour which provides good contrast against the background colour of the surface on which they are marked, preferably white.</p>			
<p>12.2.5.3</p>	<p>LIGHTS</p> <p>(a) GENERAL</p> <p><i>Note 1.— See Nig. CARs Part 12 ,Volume I, 12.2.5.3(a), concerning specifications on screening of non-aeronautical ground lights, and design of elevated and inset lights.</i></p>			



STATEMENT OF COMPLIANCE

	<p><i>Note 2.— In the case of helidecks and heliports located near navigable waters, consideration needs to be given to ensuring that aeronautical ground lights do not cause confusion to mariners.</i></p> <p><i>Note 3.— As helicopters will generally come very close to extraneous light sources, it is particularly important to ensure that, unless such lights are navigation lights exhibited in accordance with international regulations, they are screened or located so as to avoid direct and reflected glare.</i></p> <p><i>Note 4.— Systems addressed in paragraphs 12.2.5.3(d), 12.2.5.3(f), 12.2.5.3(g) and 12.2.5.3(h) are designed to provide effective lighting cues based on night conditions. Where lights are to be used in conditions other than night (i.e. day or twilight), it may be necessary to increase the intensity of the lighting to maintain effective visual cues by use of a suitable brilliancy control. Guidance is provided in the Aerodrome Design Manual (Doc 9157), Part 4.</i></p> <p><i>Note 5.— The specifications for marking and lighting of obstacles included in Nig CARs Part 12, Volume I, section 12.2.6, are equally applicable to heliports and winching areas.</i></p> <p><i>Note 6.— In cases where operations into a heliport are to be conducted at night with night vision imaging systems (NVIS), it is important to establish the compatibility of the NVIS with all heliport lighting through an assessment by the helicopter operator prior to use.</i></p> <p>(b) HELIPORT BEACON</p> <p>APPLICATION</p> <p>(1) A heliport beacon shall be provided at a heliport where:</p> <p>(i) long-range visual guidance is considered necessary and is not provided by other visual means; or</p> <p>(ii) identification of the heliport is difficult due to surrounding lights.</p> <p>LOCATION</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>(2) The heliport beacon shall be located on or adjacent to the heliport preferably at an elevated position and so that it does not dazzle a pilot at short range.</p> <p><i>Note.— Where a heliport beacon is likely to dazzle pilots at short range, it may be switched off during the final stages of the approach and landing.</i></p> <p>CHARACTERISTICS</p> <p>(3) The heliport beacon shall emit repeated series of equispaced short duration white flashes in the format in Figure 5-11.</p> <p>(4) The light from the beacon shall show at all angles of azimuth.</p> <p>(5) The effective light intensity distribution of each flash should be as shown in Figure 5-12, Illustration 1.</p> <p><i>Note.— Where brilliancy control is desired, settings of 10 per cent and 3 per cent have been found to be satisfactory. In addition, shielding may be necessary to ensure that pilots are not dazzled during the final stages of the approach and landing.</i></p> <p>(c) APPROACH LIGHTING SYSTEM</p> <p>APPLICATION</p> <p>(1) An approach lighting system shall be provided at a heliport where it is desirable and practicable to indicate a preferred approach direction.</p> <p>LOCATION</p> <p>(2) The approach lighting system shall be located in a straight line along the preferred direction of approach.</p> <p>CHARACTERISTICS</p> <p>(3) An approach lighting system shall consist of a row of three lights spaced uniformly at 30 m intervals and of a crossbar 18 m in length at a distance of 90 m from the perimeter of the FATO as shown in Figure 5-13. The lights forming the crossbar should be as nearly as practicable in a horizontal straight line at right angles to, and bisected by, the line of the centre line lights and spaced at 4.5 m intervals. Where there is the</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>need to make the final approach course more conspicuous, additional lights spaced uniformly at 30 m intervals should be added beyond the crossbar. The lights beyond the crossbar may be steady or sequenced flashing, depending upon the environment.</p> <p><i>Note.— Sequenced flashing lights may be useful where identification of the approach lighting system is difficult due to surrounding lights.</i></p> <p>(4) The steady lights shall be omnidirectional white lights. (5) Sequenced flashing lights shall be omnidirectional white lights. (6) The flashing lights shall have a flash frequency of one per second and their light distribution shall be as shown in Figure 5-12, Illustration 3. The flash sequence should commence from the outermost light and progress towards the crossbar. (7) A suitable brilliancy control shall be incorporated to allow for adjustment of light intensity to meet the prevailing conditions. <i>Note.- The following settings have been found suitable:</i> (a) Steady lights – 100 percent, 30 per cent and 10 per cent; and (b) Flashing lights – 100 per cent, 10 per cent and 3 per cent.</p> <p>(d) FLIGHT PATH ALIGNMENT GUIDANCE LIGHTING SYSTEM. (1) Intentionally left blank</p> <p>LOCATION (2) The flight path alignment guidance lighting system shall be in a straight line along the direction(s) of approach and/or departure path on one or more of the TLOF, FATO, safety area or any suitable surface in the immediate vicinity of the FATO, TLOF or safety area. (3) Intentionally left blank (4) Intentionally left blank (5) The lights shall be steady omnidirectional inset white lights. (6) Intentionally left blank (7) Intentionally left blank</p> <p>(e) VISUAL ALIGNMENT GUIDANCE SYSTEM</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p><i>Note.— The objective of a visual alignment guidance system is to provide conspicuous and discrete cues to assist the pilot to attain and maintain a specified approach track to a heliport. Guidance on suitable visual alignment guidance systems is given in the Heliport Manual (Doc 9261).</i></p> <p>(1) Intentionally left blank</p> <p>(f) VISUAL APPROACH SLOPE INDICATOR</p> <p><i>Note.— The objective of a visual approach slope indicator is to provide conspicuous and discrete colour cues, within a specified elevation and azimuth, to assist the pilot to attain and maintain the approach slope to a desired position within a FATO. Guidance on suitable visual approach slope indicators is given in the Heliport Manual (Doc 9261).</i></p> <p>(1) Intentionally left blank</p> <p>(f) FATO LIGHTING SYSTEMS FOR ONSHORE SURFACE-LEVEL HELIPORTS</p> <p><i>Note.— The objective of a FATO lighting system for onshore surfacelevel heliports is to provide to the pilot operating at night an indication of the shape, location and extent of the FATO.</i></p> <p>APPLICATION</p> <p>(1) Where a FATO with a solid surface is established at a surface-level heliport intended for use at night, FATO lights shall be provided except that they may be omitted where the FATO and the TLOF are nearly coincidental or the extent of the FATO is self-evident.</p> <p>LOCATION</p> <p>(2) FATO lights shall be placed along the edges of the FATO. The lights shall be uniformly spaced as follows:</p> <p>(i) for an area in the form of a square or rectangle, at intervals of not more than 50 m with a minimum of four lights on each side including a light at each corner; and</p> <p>(ii) for any other shaped area, including a circular area, at intervals of not more than 5 m with a minimum of ten lights.</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>CHARACTERISTICS (3) FATO lights shall be fixed omnidirectional lights showing white. Where the intensity of the lights is to be varied, the lights shall show variable white. (4) Intentionally left blank (5) Intentionally left blank (h) AIMING POINT LIGHTS</p> <p><i>Note.— The objective of aiming point lights is to provide a visual cue indicating to the pilot by night the preferred approach/departure direction, the point to which the helicopter approaches to a hover before positioning to a TLOF where a touchdown can be made, and that the surface of the FATO is not intended for touchdown.</i></p> <p>(1) Intentionally left blank</p> <p>LOCATION (2) Aiming point lights shall be collocated with the aiming point marking.</p> <p>CHARACTERISTICS (3) Aiming point lights shall form a pattern of at least six omnidirectional white lights as shown in Figure 5 -7. The lights shall be inset when a light extending above the surface could endanger helicopter operations. (3) Intentionally left blank</p> <p>(j) TLOF LIGHTING SYSTEM</p> <p><i>Note.— The objective of a TLOF lighting system is to provide illumination of the TLOF and required elements within. For a TLOF located in a FATO, the objective is to provide discernibility to the pilot, on a final approach, of the TLOF and required elements within; while for a TLOF located on an elevated heliport, shipboard heliport or helideck, the objective is visual acquisition from a defined range and to provide sufficient shape cues to permit an appropriate approach angle to be established.</i></p> <p>APPLICATION (1) A TLOF lighting system shall be provided at a heliport intended for use at night.</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p><i>Note.— Where a TLOF is located in a stand, the objective may be met with the use of ambient lighting or stand floodlighting.</i></p> <p>(2) For a surface-level heliport, lighting for the TLOF in a FATO shall consist of one or more of the following:</p> <ul style="list-style-type: none">(i) perimeter lights;(ii) floodlighting;(iii) arrays of segmented point source lighting (ASPSL) or luminescent panel (LP) lighting to identify the TLOF when (i) and (ii) are not practicable and FATO lights are available. <p>(3) For an elevated heliport, shipboard heliport or helideck, lighting for the TLOF in a FATO shall consist of:</p> <ul style="list-style-type: none">(i) perimeter lights; and(ii) ASPSL and/or LPs to identify the TDPM and/or floodlighting to illuminate the TLOF. <p><i>Note.— At elevated heliports, shipboard heliports and helidecks, surface texture cues within the TLOF are essential for helicopter positioning during the final approach and landing. Such cues can be provided using various forms of lighting (ASPSL, LP, floodlights or a combination of these lights, etc.) in addition to perimeter lights. Best results have been demonstrated by the combination of perimeter lights and ASPSL in the form of encapsulated strips of light emitting diodes n (LEDs) and inset lights to identify the TDPM and heliport identification markings.</i></p> <p>(4) Intentionally left blank</p> <p>LOCATION</p> <p>(4) TLOF perimeter lights shall be placed along the edge of the area designated for use as the TLOF or within a distance of 1.5 m from the edge. Where the TLOF is a circle, the lights shall be:</p> <ul style="list-style-type: none">(i) located on straight lines in a pattern which will provide information to pilots on drift displacement; and(ii) where (i) is not practicable, evenly spaced around the perimeter of the TLOF at the appropriate interval, except that over a sector of 45 degrees the lights shall be spaced at half spacing.			
--	---	--	--	--



STATEMENT OF COMPLIANCE

(6) TLOF perimeter lights shall be uniformly spaced at intervals of not more than 3 m for elevated heliports and helidecks and not more than 5 m for surface-level heliports. There shall be a minimum number of four lights on each side including a light at each corner. For a circular TLOF where lights are installed in accordance with 12.2.5.3(i)(5)(ii), there shall be a minimum of fourteen lights.

Note.— Guidance on this issue is contained in the Heliport Manual (Doc 9261).

(7) The TLOF perimeter lights shall be installed at an elevated heliport or fixed helideck such that the pattern cannot be seen by the pilot from below the elevation of the TLOF.

(8) The TLOF perimeter lights shall be installed on a moving helideck or shipboard heliport such that the pattern cannot be seen by the pilot from below the elevation of the TLOF when the helideck or shipboard heliport is level.

(9) On surface-level heliports, ASPSL or LPs, if provided to identify the TLOF, shall be placed along the marking designating the edge of the TLOF. Where the TLOF is a circle, they shall be located on straight lines circumscribing the area.

(10) On surface-level heliports, the minimum number of LPs on a TLOF shall be nine. The total length of LPs in a pattern shall not be less than 50 per cent of the length of the pattern. There shall be an odd number with a minimum number of three panels on each side of the TLOF including a panel at each corner. LPs shall be uniformly spaced with a distance between adjacent panel ends of not more than 5 m on each side of the TLOF.

(11) Intentionally left blank

(12) TLOF floodlights shall be located so as to avoid glare to pilots in flight or to personnel working on the area. The arrangement and aiming of floodlights shall be such that shadows are kept to a minimum.

Note.— ASPSL and LPs used to designate the TDPM and/or heliport identification marking have been shown to provide enhanced surface texture cues when compared to low-level floodlights. Due to the risk of misalignment, if floodlights are used, there will be a need for them to be



STATEMENT OF COMPLIANCE

	<p><i>checked periodically to ensure they remain within the specifications contained within 12.2.5.3.(i).</i></p> <p>CHARACTERISTICS</p> <p>(13) The TLOF perimeter lights shall be fixed omnidirectional lights showing green.</p> <p>(14) At a surface-level heliport, ASPSL or LPs shall emit green light when used to define the perimeter of the TLOF.</p> <p>(15) Intentionally left blank</p> <p>(16) An LP shall have a minimum width of 6 cm. The panel housing shall be the same colour as the marking it defines.</p> <p>(17) For a surface-level or elevated heliport, the TLOF perimeter lights located in a FATO shall not exceed a height of 5 cm and shall be inset when a light extending above the surface could endanger helicopter operations.</p> <p>(18) For a helideck or shipboard heliport, the TLOF perimeter lights shall not exceed a height of 5 cm, or for a FATO/TLOF, 15 cm.</p> <p>(19) Intentionally left blank</p> <p>(20) For a helideck or shipboard heliport, the TLOF floodlights shall not exceed a height of 5 cm, or for a FATO/TLOF, 15 cm.</p> <p>(21) The LPs shall not extend above the surface by more than 2.5 cm.</p> <p>(22) Intentionally left blank</p> <p>(23) Intentionally left blank</p> <p>(24) The spectral distribution of TLOF floodlights shall be such that the surface and obstacle markings can be correctly identified.</p> <p>(25) Intentionally left blank</p> <p>(26) Intentionally left blank</p> <p>(27) Intentionally left blank</p> <p>(j) HELICOPTER STAND FLOODLIGHTING</p> <p><i>Note.— The objective of helicopter stand floodlighting is to provide illumination of the stand surface and associated markings to assist the manoeuvring and positioning of a helicopter and facilitation of essential operations around the helicopter.</i></p> <p>APPLICATION</p> <p>(1) Helicopter stand floodlighting shall be provided on a helicopter stand</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>intended to be used at night.</p> <p><i>Note.— Guidance on stand floodlighting is given in the apron floodlighting section in the Aerodrome Design Manual (Doc 9157), Part 4</i></p> <p>LOCATION</p> <p>(2) Helicopter stand floodlights shall be located so as to provide adequate illumination, with a minimum of glare to the pilot of a helicopter in flight and on the ground, and to personnel on the stand . The arrangement and aiming of floodlights should be such that a helicopter stand receives light from two or more directions to minimize shadows.</p> <p>CHARACTERISTICS</p> <p>(3) The spectral distribution of stand floodlights shall be such that the colours used for surface and obstacle marking can be correctly identified.</p> <p>(4) Horizontal and vertical illuminance shall be sufficient to ensure that visual cues are discernible for required manoeuvring and positioning, and essential operations around the helicopter can be performed expeditiously without endangering personnel or equipment.</p> <p>(k) WINCHING AREA FLOODLIGHTING</p> <p><i>Note.— The objective of winching area floodlighting is to provide illumination of the surface and obstacles, and visual cues to assist a helicopter to be positioned over, and retained within, an area from which a passenger or equipment can be lowered or raised.</i></p> <p>APPLICATION</p> <p>(1) Winching area floodlighting shall be provided at a winching area intended for use at night.</p> <p>LOCATION</p> <p>(2) Winching area floodlights shall be located so as to avoid glare to pilots in flight or to personnel working on the area. The arrangement and aiming of floodlights shall be such that shadows are kept to a minimum.</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>CHARACTERISTICS (3) The spectral distribution of winching area floodlights shall be such that the surface and obstacle markings can be correctly identified. (4) Intentionally left blank</p> <p>(l) TAXIWAY LIGHTS</p> <p><i>Note.— The specifications for taxiway centre line lights and taxiway edge lights in Nig. CARs Part 12, Volume I, 12.2.5.3(q) and 12.2.5.3(r), are equally applicable to taxiways intended for ground taxiing of helicopters.</i></p> <p>(m) VISUAL AIDS FOR DENOTING OBSTACLES OUTSIDE AND BELOW THE OBSTACLE LIMITATION SURFACE</p> <p><i>Note.— Arrangements for an aeronautical study of objects outside the obstacle limitation surface and for other objects are addressed in Nig. CARs Part 12, Volume I, section 12.2.4.</i></p> <p>(1) Intentionally left blank (2) Intentionally left blank</p> <p>(n) FLOODLIGHTING OF OBSTACLES</p> <p>APPLICATION (1) At a heliport intended for use at night, obstacles shall be floodlighted if it is not possible to display obstacle lights on them.</p> <p>LOCATION (2) Obstacle floodlights shall be arranged so as to illuminate the entire obstacle and as far as practicable in a manner so as not to dazzle pilots. (3) Intentionally left blank</p>			
12.2.6	HELIPORT EMERGENCY RESPONSE			



STATEMENT OF COMPLIANCE

<p>12.2.6.1</p>	<p>HELIPORT EMERGENCY PLANNING</p> <p><i>Introductory Note.— Heliport emergency planning is the process of preparing a heliport to cope with an emergency that takes place at the heliport or in its vicinity. Examples of emergencies include crashes on or off the heliport, medical emergencies, dangerous goods occurrences, fires and natural disasters. The purpose of heliport emergency planning is to minimize the impact of an emergency by saving lives and maintaining helicopter operations. The heliport emergency plan sets out the procedures for coordinating the response of heliport agencies or services (air traffic services unit, firefighting services, heliport administration, medical and ambulance services, aircraft operators, security services and police) and the response of agencies in the surrounding community (fire departments, police, medical and ambulance services, hospitals, military, and harbour patrol or coast guard) that could be of assistance in responding to the emergency.</i></p> <p>(a) A heliport emergency plan shall be established commensurate with the helicopter operations and other activities conducted at the heliport.</p> <p>(b) The plan shall identify agencies which could be of assistance in responding to an emergency at the heliport or in its vicinity.</p> <p>(c) The heliport emergency plan shall provide for the coordination of the actions to be taken in the event of an emergency occurring at a heliport or in its vicinity.</p> <p>(d) Where an approach/departure path at a heliport is located over water, the plan shall identify which agency is responsible for coordinating rescue in the event of a helicopter ditching and indicate how to contact that agency.</p> <p>(e) The plan shall include, as a minimum, the following information:</p> <ol style="list-style-type: none"> (1) the types of emergencies planned for; (2) how to initiate the plan for each emergency specified; (3) the name of agencies on and off the heliport to contact for each type of emergency with telephone numbers or other contact information; (4) the role of each agency for each type of emergency; 			
-----------------	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>(5) a list of pertinent on-heliport services available with telephone numbers or other contact information;</p> <p>(6) copies of any written agreements with other agencies for mutual aid and the provision of emergency services; and</p> <p>(7) a grid map of the heliport and its immediate vicinity.</p> <p>(f) All agencies identified in the plan shall be consulted about their role in the plan.</p> <p>(g) The plan shall be reviewed and the information in it updated at least yearly or, if deemed necessary, after an actual emergency, so as to correct any deficiency found during an actual emergency.</p> <p>(h) A test of the emergency plan shall be carried out at least once every three years.</p>			
<p>12.2.6.2</p>	<p>RESCUE AND FIREFIGHTING</p> <p><i>Introductory Note.— It is important this section be read in conjunction with the appropriate detailed guidance on rescue and firefighting options given in the Heliport Manual (Doc 9261).</i></p> <p><i>Provisions described in this section are intended to address incidents or accidents within the heliport response area only. No dedicated firefighting provisions are included for helicopter accidents or incidents that may occur outside the response area, such as on an adjacent roof near an elevated heliport.</i></p> <p><i>Complementary agents are ideally dispensed from one or two extinguishers (although more extinguishers may be permitted where high volumes of an agent are specified, e.g. H3 operations). The discharge rate of complementary agents needs to be selected for optimum effectiveness of the agent used. When selecting dry chemical powders for use with foam, care needs to be exercised to ensure compatibility.</i></p> <p><i>Complementary agents need to comply with the appropriate specifications of the International Organization for Standardization (ISO).</i></p> <p><i>Where a fixed monitor system (FMS) is installed, trained monitor operators, where provided, are positioned on at least the upwind</i></p>			



STATEMENT OF COMPLIANCE

	<p><i>location to ensure primary media is directed to the seat of the fire. For a ringmain system (RMS) practical testing has indicated that these solutions are only guaranteed to be fully effective for TLOFs up to 20 m diameter.</i></p> <p><i>If the TLOF is greater than 20 m, an RMS should not be considered unless supplemented by other means to distribute primary media (e.g. additional pop-up nozzles installed in the centre of the TLOF).</i></p> <p><i>The International Convention for the Safety of Life at Sea (SOLAS) sets forth provisions on rescue and firefighting (RFF) arrangements for purpose-built and non-purpose-built shipboard heliports in SOLAS regulations II 2/18, II-2-Helicopter Facilities, and the SOLAS Fire Safety Systems Code.</i></p> <p><i>It may therefore be assumed that this chapter does not include RFF arrangements for purpose built or non-purpose-built shipboard heliports or for winching areas.</i></p> <p>(a) APPLICABILITY</p> <p>The following specifications shall apply to new builds or replacement of existing systems or part thereof from 1 January 2023: 12.2.6.2(b)(1), 12.2.6.2(c)(3), 12.2.6.2(c)(4), 12.2.6.2(c)(6), 12.2.6.2(c)(7), 12.2.6.2(c)(9), 12.2.6.2(c)(10), 12.2.6.2(c)(12), 12.2.6.2(c)(13) and 12.2.6.2(d)(2)</p> <p><i>Note.— For areas for the exclusive use of helicopters at aerodromes primarily for the use of aeroplanes, distribution of extinguishing agents, response time, rescue equipment and personnel have not been considered in this section. See Nig. CARs Part 12, Volume I, Section 12.2.9.</i></p> <p>(1) Rescue and firefighting equipment and services shall be provided at helidecks and at elevated heliports located above occupied structures.</p> <p>(2) A safety risk assessment shall be performed to determine the need for RFF equipment and services at surface-level heliports and elevated heliports located above unoccupied structures.</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

Note.— Further guidance on factors to inform the safety risk assessment, including staffing models for heliports with only occasional movements and examples of unoccupied areas that may be located beneath elevated heliports, is given in the Heliport Manual (Doc 9261).

(b) LEVEL OF PROTECTION PROVIDED

(1) For the application of primary media, the discharge rate (in litres/minute) applied over the assumed practical critical area (in m²) shall be predicated on a requirement to bring any fire which may occur on the heliport under control within one minute, measured from activation of the system at the appropriate discharge rate.

Practical critical area calculation where primary media is applied as a solid stream

Note.— This section is not applicable to helidecks regardless of how primary media is being delivered.

(2) The practical critical area should be calculated by multiplying the helicopter fuselage length (m) by the helicopter fuselage width (m) plus an additional width factor (W1) of 4 m. Categorization from H0 to H3 should be determined on the basis of the fuselage dimensions in Table 6 -1.

Note 1.— For helicopters which exceed one or both of the dimensions for a category H3 heliport, it will be necessary to recalculate the level of protection using practical critical area assumptions based on the actual fuselage length and the actual fuselage width of the helicopter plus an additional width factor (W1) of 6 m.

Note 2.— The practical critical area may be considered on a helicopter type-specific basis by using the formula in 12.2.6.2(b)(2) Guidance on practical critical area in relation to the heliport firefighting category is given in the Heliport Manual (Doc 9261) where a discretionary 10 per cent tolerance on fuselage dimension “upper limits” is applied.

(3) For heliports, except helidecks, the practical critical area shall be based on an area contained within the heliport perimeter, which always includes the TLOF, and to the extent that it is load-bearing, the FATO.



STATEMENT OF COMPLIANCE

(4) For helidecks, the practical critical area shall be based on the largest circle capable of being accommodated within the TLOF perimeter.

Note.— Paragraph 12.2.6.2(b)(4) is applied for the practical critical area calculation for helidecks regardless of how primary media is being delivered.

(b) EXTINGUISHING AGENTS

Note 1.— Throughout section 12.2.6.2(c), the discharge rate of a performance level B foam is assumed to be based on an application rate of 5.5 L/min/m², and for a performance level C foam and for water, is assumed to be based on an application rate of 3.75 L/min/m². These rates may be reduced if, through practical testing, a Authority demonstrates that the objectives of 12.2.6.2(b)(1) can be achieved for a specific foam use at a lower discharge rate (L/min).

Note 2.— Information on the required physical properties and fire extinguishing performance criteria needed for a foam to achieve an acceptable performance level B or C rating is given in the Airport Services Manual (Doc 9137), Part 1.

Surface level heliports with primary media applied as a solid stream using a portable foam application system (PFAS) Note.— Except for a limited-sized surface-level heliport, the assumption is made that foam dispensing equipment will be transported to the incident or accident location on an appropriate vehicle (PFAS).

(1) Where a rescue and firefighting service (RFFS) is provided at a surface-level heliport, the amount of primary media and complementary agents shall be in accordance with Table 6-2.

Note.— The minimum discharge duration in Table 6-2 is assumed to be two minutes. However, if the availability of back-up specialist fire services is remote from the heliport, consideration may need to be given to increasing the discharge duration from two minutes to three minutes.



STATEMENT OF COMPLIANCE

	<p>Elevated heliports with primary media applied as a solid stream using a fixed foam application system (FFAS)</p> <p><i>Note.— The assumption is made that primary media (foam) will be delivered through a fixed foam application system such as an FMS.</i></p> <p>(3) <i>Where an RFFS is provided at an elevated heliport, the amount of foam media and complementary agents shall be in accordance with Table 6 -3.</i></p> <p><i>Note 1.— The minimum discharge duration in Table 6-3 is assumed to be five minutes.</i></p> <p><i>Note 2.— For guidance on the provision of additional hand controlled foam branches for the application of aspirated foam, see the Heliport Manual (Doc 9261).</i></p> <p>Elevated heliports/limited-sized surface-level heliports with primary media applied in a dispersed pattern through an FFAS — a solid-plate heliport</p> <p>(3) The amount of water required for foam production shall be predicated on the practical critical area (m²) multiplied by the appropriate application rate (L/min/m²), giving a discharge rate for foam solution (in L/min). The discharge rate should be multiplied by the discharge duration to calculate the amount of water needed for foam production.</p> <p>(4) The discharge duration shall be at least three minutes.</p> <p>(5) Complementary media shall be in accordance with Table 6-3, for H2 operations.</p> <p><i>Note.— For helicopters with a fuselage length greater than 16 m and/or a fuselage width greater than 2.5 m, complementary media in Table 6-3 for H3 operations may be considered.</i></p> <p>Purpose-built elevated heliports/limited-sized surface-level heliports with primary media applied in a dispersed pattern through a fixed application system (FAS) — a passive fire retarding surface with water-only deck integrated firefighting system (DIFFS)</p>			
--	---	--	--	--



STATEMENT OF COMPLIANCE

	<p>(6) The amount of water required shall be predicated on the practical critical area (m²) multiplied by the appropriate application rate (3.75 L/min/m²) giving a discharge rate for water (in L/min). The discharge rate should be multiplied by the discharge duration to determine the total amount of water needed.</p> <p>(7) The discharge duration shall be at least two minutes.</p> <p>(8) Complementary media shall be in accordance with Table 6-3 for H2 operations.</p> <p><i>Note.— For helicopters with a fuselage length greater than 16 m and/or a fuselage width greater than 2.5 m, complementary media for H3 operations may be considered.</i></p> <p>Purpose-built helidecks with primary media applied in a solid stream or a dispersed pattern through a fixed foam application system (FFAS) — a solid-plate heliport</p> <p>(9) The amount of water required for foam media production shall be predicated on the practical critical area (m²) multiplied by the application rate (L/min/m²) giving a discharge rate for foam solution (in L/min). The discharge rate should be multiplied by the discharge duration to calculate the amount of water needed for foam production.</p> <p>(10) The discharge duration shall be at least five minutes.</p> <p>(11) Complementary media shall be in accordance with Table 6-3 to H0 levels for helidecks up to and including 16.0 m and to H1/H2 levels for helidecks greater than 16.0 m. Helidecks greater than 24 m should adopt H3 levels.</p> <p><i>Note.— For guidance on the provision of additional hand-controlled foam branches for the application of aspirated foam, see the Heliport Manual (Doc 9261).</i></p> <p>Purpose-built helidecks with primary media applied in a dispersed pattern through an FAS — a passive fire-retarding surface with water-only DIFFS</p> <p>(12) The amount of water required shall be predicated on the practical critical area (m²) multiplied by the application rate (3.75 L/min/m²) giving a discharge rate for water (in L/min). The discharge rate should</p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>be multiplied by the discharge duration to calculate the amount of water needed.</p> <p><i>Note.— Sea-water may be used.</i></p> <p>(13) The discharge duration shall be at least three minutes. (14) Complementary media shall be in accordance with Table 6-3 to H0 levels for helidecks up to and including 16.0 m and to H1/H2 levels for helidecks greater than 16.0 m. Helidecks greater than 24 m should adopt H3 levels.</p> <p>(c) RESPONSE TIME</p> <p>(1) At surface-level heliports, the operational objective of the RFF response shall be to achieve response times not exceeding two minutes in optimum conditions of visibility and surface conditions.</p> <p><i>Note.— Response time is considered to be the time between the initial call to the RFFS and the time when the first responding vehicle(s) (the service) is (are) in position to apply foam at a rate of at least 50 per cent of the discharge rate specified in Table 6-2.</i></p> <p>(2) At elevated heliports, limited-sized surface-level heliports and helidecks, the response time for the discharge of primary media at the required application rate shall be 15 seconds measured from system activation. If RFF personnel are needed, they should be immediately available on or in the vicinity of the heliport while helicopter movements are taking place.</p> <p>(e) RESCUE ARRANGEMENTS Rescue arrangements commensurate with the overall risk of the helicopter operation shall be provided at the heliport.</p> <p><i>Note.— Guidance on rescue arrangements, e.g. options for rescue and for personal protective equipment to be provided at a heliport, is given in the Heliport Manual (Doc 9261).</i></p>			
--	--	--	--	--



STATEMENT OF COMPLIANCE

	<p>(f) COMMUNICATION AND ALERTING SYSTEM A suitable alerting and/or communication system shall be provided in accordance with the emergency response plan.</p> <p>(g) PERSONNEL</p> <p><i>Note.— The provision of RFF personnel may be determined by use of a task/resource analysis. Guidance is given in the Heliport Manual (Doc 9261).</i></p> <p>(1) Where provided, the number of RFF personnel shall be sufficient for the required task. (2) Where provided, RFF personnel shall be trained to perform their duties, and maintain their competence. (3) Rescue and firefighting personnel shall be provided with protective equipment.</p> <p>(h) MEANS OF ESCAPE</p> <p>(1) Elevated heliports and helidecks shall be provided with a main access and at least one additional means of escape. (2) Access points shall be located as far apart from each other as is practicable.</p> <p><i>Note.— The provision of an alternative means of escape is necessary for evacuation and for access by RFF personnel. The size of an emergency access/egress route may require consideration of the number of passengers and of special operations such as helicopter emergency medical services that require passengers to be carried on stretchers or trolleys.</i></p>			
12.2.7	INSTRUMENT HELIPORTS WITH NON-PRECIS APPROACHES AND INSTRUMENT DEPARTURES			
12.2.7.1	<p>Applicability</p> <p>(a) This subsection prescribe the physical characteristics and obstacle limitation surfaces to be provided for at heliports, and certain facilities and technical services normally provided at a</p>			



STATEMENT OF COMPLIANCE

	<p>heliport. It is not intended that these specifications limit or regulate the operation of an aircraft.</p> <p>(b) The specifications in this section describe additional conditions beyond those found in the previous provisions of Nig. CARs Part 12, Volume II, that apply to instrument heliports with non-precision and/or precision approaches.</p> <p>(c) All specifications contained within this subsections of Nig. CARs Part 12, Volume II, are equally applicable to instrument heliports, but with reference to further provisions described IS:12.2.7.</p>			
--	---	--	--	--